

# COLUMBIA COUNTY BUILDING DEPARTMENT RESIDENTIAL CHECK LIST

MINIMUM PLAN REQUIREMENTS: FLORIDA BUILDING CODE RESIDENTIAL 2017 EFFECTIVE 1 JANUARY 2018
AND THE NATIONAL ELECTRICAL 2014 EFFECTIVE 1 JANUARY 2018

#### ALL REQUIREMENTS ARE SUBJECT TO CHANGE

ALL BUILDING PLANS MUST INDICATE COMPLIANCE WITH THE CURRENT FLORIDA BUILDING CODES RESIDENTIAL AND THE NATIONAL ELECTRICAL CODE. ALL PLANS OR DRAWINGS SHALL PROVIDE CALCULATIONS AND DETAILS THAT HAVE THE SEAL AND SIGNATURE OF A CERTIFIED ARCHITECT OR ENGINEER REGISTERED IN THE STATE OF FLORIDA, OR ALTERNATE METHODOLOGIES, APPROVED BY THE STATE OF FLORIDA BUILDING COMMISSION FOR ONE-AND-TWO FAMILY DWELLINGS, FBC 1609.3.1 THRU 1609.3.3.

FOR DESIGN PURPOSES THE FOLLOWING BASIC WIND SPEEDS ARE PER FLORIDA BUILDING CODE FIGURE 1609-A
THROUGH 1609-C ULTIMATE DESIGN WIND SPEEDS FOR RISK CATEGORY AND BUILDINGS AND OTHER STRUCTURES
Revised 7/1/18

		GENERAL REQUI	yfla.com/BuildingandZoning.asp  REMENTS:  CABLE BOXES BEFORE SUBMITTAL	Sele	Each Box shall be Circled as Applicable Select From Drop dow			
1 2	Two (2) complete sets of pla		wing: , details that are not used shall be marked void	V				
3	Condition space (Sq. Ft.)		Total (Sq. Ft.) under roof	_	Yes No			

Designers name and signature shall be on all documents and a licensed architect or engineer, signature and official embossed seal shall be affixed to the plans and documents as per the FLORIDA BUILDING CODES RESIDENTIAL 107.1.

Site Plan information including:

19

20

Number of stories

	4	Dimensions of lot or parcel of land	Yes	▼	
Г	5	Dimensions of all building set backs	Yes	<b>T</b>	
	6	Location of all other structures (include square footage of structures) on parcel, existing or proposed well and septic tank and all utility easements.	Yes	▼	
Г	7	Provide a full legal description of property.	NA	▼	

#### Wind-load Engineering Summary, calculations and any details are required.

Building height from the established grade to the roofs highest peak

		ns to Inclu Box shal Circled as oplicable	ll be
Plans or specifications must show compliance with FBCR Chapter 3	Yes	No	NA
	Select Fr	om Drop	down
Basic wind speed (3-second gust), miles per hour	Yes		
(Wind exposure – if more than one wind exposure is used, the wind exposure and applicable wind direction shall be indicated)	Yes		
Wind importance factor and nature of occupancy	Yes		
The applicable internal pressure coefficient, Components and Cladding	Yes		
The design wind pressure in terms of psf (kN/m²), to be used for the design of exterior components cladding materials not specifally designed by the registered design professional.			▼
levations Drawing including:			
All side views of the structure	Yes		
5 Roof pitch	Yes		
Overhang dimensions and detail with attic ventilation	Yes		▼
Location, size and height above roof of chimneys	NA		
Location and size of skylights with Florida Product Approval	NA		▼

Yes

Floor Plan Including:

_			
21	Dimensioned area plan showing rooms, attached garage, breeze ways, covered porches, deck, balconies	Yes	▼
22	Raised floor surfaces located more than 30 inches above the floor or grade	NA	_
23	All exterior and interior shear walls indicated	Yes	<b>T</b>
24	Shear wall opening shown (Windows, Doors and Garage doors)	Yes	₹
25	Show compliance with Section FBCR 310 Emergency escape and rescue opening shown in each		
	bedroom (net clear opening shown) and Show compliance with Section FBC 1405.13.2 where the opening of an operable window is located more than 72 inches above the finished grade or surface below, the lowest part of the clear opening of the window shall be a minimum of 24 inches above the finished floor of the room in which the window is located. Glazing between the floor and 24 inches shall be fixed or have openings through which a 4-inch-diameter sphere cannot pass.	Yes	▼
26	Safety glazing of glass where needed	Yes	
27	Fireplaces types (gas appliance) (vented or non-vented) or wood burning with Hearth (see chapter 10 and chapter 24 of FBCR)	Yes	
28	Show stairs with dimensions (width, tread and riser and total run) details of guardrails, Handrails	NA	▾
29	Identify accessibility of bathroom (see FBCR SECTION 320)	NA	✓

All materials placed within opening or onto/into exterior walls, soffits or roofs shall have Florida product approval number and mfg. installation information submitted with the plans (see Florida product approval form)

**GENERAL REQUIREMENTS:** 

FBCR 606: Masonry Walls and Stem walls (load bearing & shear Walls)

38 Show all materials making up walls, wall height, and Block size, mortar type

39 Show all Lintel sizes, type, spans and tie-beam sizes and spacing of reinforcement

APPLICANT – PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL	Each Box s Circled Applica	as
FBCR 403: Foundation Plans		
	Select From	Drop dow
30 Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size and type of reinforcing.	Yes	
31 All posts and/or column footing including size and reinforcing	Yes	▼
32 Any special support required by soil analysis such as piling.	NA	
33 Assumed load-bearing valve of soil Pound Per Square Foot	NA NA	
Location of horizontal and vertical steel, for foundation or walls (include # size and type) For s with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an grounding electrode system. Per the National Electrical Code article 250.52.3	e	•
FBCR 506: CONCRETE SLAB ON GRADE	4 1	
Show Vapor retarder (6mil. Polyethylene with pints la pd 6 inches and sealed)	Yes	▼
Show control j oints, synthetic fiber reinforcement or welded fire fabric reinforcement and Spp	orts Yes	▼
FBCR 318: PROTECTION AGAINST TERMITES  Indicate on the foundation plan if soil treatment is used for subterranean termite prevention or		
37 Submit other approved termite protection methods. <b>Protection shall be provided by registered</b> termiticides	Yes	▼

Metal frame shear wall and roof systems shall be designed, signed and sealed by Florida Prof. Engineer or Architect

Items to Include-

NA

NA

Floor Framing System: First and/or second story

-		13-140	
40	Floor truss package shall including layout and details, signed and sealed by Florida Registered Professional Engineer	Yes	
41	Show conventional floor joist type, size, span, spacing and attachment to load bearing walls, stem walls and/or priers	Yes	
42	Girder type, size and spacing to load bearing walls, stem wall and/or priers	Yes	
43	Attachment of joist to girder	Yes	
44	Wind load requirements where applicable	Yes	
45	Show required under-floor crawl space	NA	<b>▼</b>
46	Show required amount of ventilation opening for under-floor spaces	NA	<b>▼</b>
47	Show required covering of ventilation opening	NA	
48	Show the required access opening to access to under-floor spaces	NA	
49	Show the sub-floor structural panel sheathing type, thickness and fastener schedule on the edges & intermediate of the areas structural panel sheathing	NA	
50	Show Draftstopping, Fire caulking and Fire blocking	NA	
51	Show fireproofing requirements for garages attached to living spaces, per FBCR section 302.6	Yes	<b>▼</b>
52	Provide live and dead load rating of floor framing systems (psf).	NA	▼

FBCR CHAPTER 6 WOOD WALL FRAMING CONSTRUCTION

GENERAL REQUIREMENTS: APPLICANT – PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL	Items to Include- Each Box shall be Circled as Applicable
--	--

Select from Drop down

	Diameter 2015	cicci ii oiii	Drop down
53	Stud type, grade, size, wall height and oc spacing for all load bearing or shear walls	Yes	
54	Fastener schedule for structural members per table FBC-R602.3.2 are to be shown	Yes	
55	Show wood structural panel's sheathing attachment to studs, joist, trusses, rafters and structural members, showing fastener schedule attachment on the edges & intermediate of the areas structural panel sheathing	Yes	T
56	Show all required connectors with a max uplift rating and required number of connectors and oc spacing for continuous connection of structural walls to foundation and roof trusses or rafter systems	Yes	▼
57	Show sizes, type, span lengths and required number of support jack studs, king studs for shear wall opening and girder or header per FBC-R602.7.	Yes	
58	Indicate where pressure treated wood will be placed	Yes	
59	Show all wall structural panel sheathing, grade, thickness and show fastener schedule for structural panel sheathing edges & intermediate areas	Yes	
60	A detail showing gable truss bracing, wall balloon framing details or/ and wall hinge bracing detail	Yes	

## **FBCR:ROOF SYSTEMS:**

61	Truss design drawing shall meet section FBC-R 802.10.1 Wood trusses	Yes	
62	Include a layout and truss details, signed and sealed by Florida Professional Engineer	Yes	
63	Show types of connector's assemblies' and resistance uplift rating for all trusses and rafters	Yes	₹
64	Show gable ends with rake beams showing reinforcement or gable truss and wall bracing details	Yes	
65	Provide dead load rating of trusses	Yes	

# FBCR 802:Conventional Roof Framing Layout

66	Rafter and ridge beams sizes, span, species and spacing	NA	
67	Connectors to wall assemblies' include assemblies' resistance to uplift rating	NA	
68	Valley framing and support details	NA	
69	Provide dead load rating of rafter system	NA	

## **FBCR 803 ROOF SHEATHING**

70	Include all materials which will make up the roof decking, identification of structural panel sheathing, grade, thickness	Yes	▼
71	Show fastener Size and schedule for structural panel sheathing on the edges & intermediate areas	Yes	Ī

**ROOF ASSEMBLIES FRC Chapter 9** 

72	Include all materials which will make up the roof assembles covering	Yes	▼
73	Submit Florida Product Approval numbers for each component of the roof assembles covering	Yes	

## FBCR Chapter 11 Energy Efficiency Code for Residential Building

Residential construction shall comply with this code by using the following compliance methods in the FBCR Chapter 11 Residential buildings compliance methods. Two of the required forms are to be submitted, N1100.1.1.1 As an alternative to the computerized Compliance Method A, the Alternate Residential Point System Method hand calculation, Alternate Form 600A, may be used. All requirements specific to this calculation are located in Sub appendix C to Appendix G. Buildings complying by this alternative shall meet all mandatory requirements of this chapter. Computerized versions of the Alternate Residential Point System Method shall not be acceptable for code compliance.

	GENERAL REQUIREMENTS: APPLICANT – PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL	Each Bo Circl Appl	Include- x shall be led as icable
	S	elect from I	Prop Down
74	Show the insulation R value for the following areas of the structure	Yes	
75	Attic space	Yes	
76	Exterior wall cavity	Yes	
77	Crawl space	NA	
Н	AC information		
<b>7</b> 8	Submit two copies of a Manual J sizing equipment or equivalent computation study	Yes	▼
79	Exhaust fans shown in bathrooms Mechanical exhaust capacity of 50 cfm intermittent or 20 cfm continuous required	Yes	▼
80	Show clothes dryer route and total run of exhaust duct	No	
Plu 81 82	All fixtures waste water lines shall be shown on the foundationplan Show the location of water heater	Yes Yes	
83 84	ivate Potable Water Pump motor horse power Reservoir pressure tank gallon capacity Rating of cycle stop valve if used	NA NA NA	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \
Ele	ectrical layout shown including		
86	Show Switches, receptacles outlets, lighting fixtures and Ceiling fans	Yes	
87	Show all 120-volt, single phase, 15- and 20-ampere branch circuits outlets required to be protected	Yes	
	by Ground-Fault Circuit Interrupter (GFCI) Article 210.8 A		
88	Show the location of smoke detectors & Carbon monoxide detectors	Yes	
89	Show service panel, sub-panel, location(s) and total ampere ratings	Yes	
90	On the electrical plans identify the electrical service overcurrent protection device for the main electrical service. This device shall be installed on the exterior of structures to serve as a disconnecting means for the utility company electrical service. Conductors used from the exterior disconnecting means to a panel or sub panel shall have four-wire conductors, of which one conductor shall be used as an equipment ground. Indicate if the utility company service entrance cable will be of the overhead or underground type.	Yes	▼
	For structures with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an Grounding electrode system. Per the National Electrical Code article 250.52.3		
91	Appliances and HVAC equipment and disconnects	Yes	
92	Show all 120-volt, single phase, 15- and 20-ampere branch circuits supplying outlets installed in dwelling unit family rooms, dining rooms, living rooms, parlors, libraries, dens, bedrooms, sunrooms, recreation rooms, closets, hallways, or similar rooms or areas shall be protected by a listed <b>Combination arc-fault circuit interrupter</b> , Protection device.	Yes	•

#### **Notice Of Commencement:**

A notice of commencement form RECORDED in the Columbia County Clerk Office is required to be filed with the Building Department BEFORE ANY INSPECTIONS can be performed.

	Items to Include-
GENERAL REQUIREMENTS: APPLICANT – PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL	Each Box shall be Circled as

### \*\*ITEMS 95, 96, & 98 Are Required After APPROVAL from the ZONING DEPT.\*\*

Select from Drop down

	So	elect from	Drop down
93	<b>Building Permit Application</b> A current Building Permit Application is to be completed, by following the Checklist all supporting documents must be submitted.  There is a \$15.00 application fee. The completed application with attached documents and application fee can be mailed.	Yes	
94	Parcel Number The parcel number (Tax ID number) from the Property Appraisers Office (386) 758-1083 is required. A copy of property deed is also required. www.columbiacountyfla.com	Yes	
95	Environmental Health Permit or Sewer Tap Approval A copy of a approved Columbia County Environmental Health (386) 758-1058	Yes	
96	City of Lake City A City Water and/or Sewer letter. Call 386-752-2031	Yes	
97	Toilet facilities shall be provided for all construction sites	Yes	▼
98	<b>Town of Fort White</b> (386) 497-2321 If the parcel in the application for building permit is within the Corporate city limits of Fort White, an approval land use development letter issued by the Town of Fort is required to be submitted with the application for a building permit.	NA	✓
99	Flood Information: All projects within the Floodway of the Suwannee or Santa Fe Rivers shall require permitting through the Suwannee River Water Management District, before submitting a application to this office. Any project located within a flood zone where the base flood elevation (100 year flood) has been established shall meet the requirements of Section 8.5.2 of the Columbia County Land Development Regulations. Any project located within a flood zone where the base flood elevation has not been established (Zone A) shall meet the requirements of Section 8.5.3 of the Columbia County Land Development Regulations (Municpde.cpm)	NA	▼
100		Yes	V
101	A Flood development permit is also required for AE, Floodway & AH. Development permit cost is \$50.00	NA	
102	<b>Driveway Connection:</b> If the property does not have an existing access to a public road, then an application for a culvert permit (\$25.00) must be made. County Public Works Dept. determines the size and length of every culvert before instillation and completes a final inspection before permanent power is granted. If the applicant feels that a culvert is not needed, they may apply for a culvert waiver (\$50.00) Separate Check when issued. If the project is to be located on an F.D.O.T. maintained road, then an F.D.O.T. access permit is required.	Yes	▼
103	<b>911 Address:</b> An application for a 911 address must be applied for and <b>received</b> through the Columbia County Emergency Management Office of 911 Addressing Department (386) 758-1125.	Yes	

Ordinance Sec. 90-75. - Construction debris. (e) It shall be unlawful for any person to dispose of or discard solid waste, including construction or demolition debris at any place within the county other than on an authorized disposal site or at the county's solid waste facilities. The temporary storage, not to exceed seven days of solid waste (excluding construction and demolition debris) on the premises where generated or vegetative trash pending disposition as authorized by law or ordinance, shall not be deemed a violation of this section. The temporary storage of construction and demolition debris on the premises where generated or vegetative trash pending disposition as authorized by law or ordinance shall not be deemed in violation of this section; provided, however, such construction and demolition debris must be disposed of in accordance with this article prior to the county's issuance of a certificate of occupancy for the premises. The burning of lumber from a construction or demolition project or vegetative trash when done so with legal and proper permits from the authorized agencies and in accordance with such agencies' rules and regulations, shall not be deemed a violation of this section. No person shall bury, throw, place, or deposit, or cause to be buried, thrown, placed, or deposited, any solid waste, special waste, or debris of any kind into or on any of the public streets, road right-of-way, highways, bridges, alleys, lanes, thoroughfares, waters, canals, or vacant lots or lands within the county. No person shall bury any vegetative trash on any of the public streets, road right-of-way, highways, bridges, lanes, thoroughfares, waters, canals, or lots less than ten acres in size within the county.