

DATE 07/01/2009

Columbia County Building Permit

This Permit Must Be Prominently Posted on Premises During Construction

PERMIT
000027921

APPLICANT B. TRENT GIEBEIG PHONE 386.397.0545

ADDRESS 697 SE HOLLY TERRACE LAKE CITY FL 32025

OWNER PETE GIEBEIG PHONE 386.397.0545

ADDRESS 170 SW VANN CT LAKE CITY FL 32024

CONTRACTOR B. TRENT GIEBEIG PHONE 386.397.0545

LOCATION OF PROPERTY 90-W TO SR. 247-S TO MAY-FAIR LN,TR TO VANN CT,TR & IT'S
THE 3RD LOT ON L.

TYPE DEVELOPMENT SFD/UTILITY ESTIMATED COST OF CONSTRUCTION 115600.00

HEATED FLOOR AREA 1608.00 TOTAL AREA 2312.00 HEIGHT 17.60 STORIES 1

FOUNDATION CONC WALLS FRAMED ROOF PITCH 6'12 FLOOR CONC

LAND USE & ZONING RSF-2 MAX. HEIGHT 35

Minimum Set Back Requirments: STREET-FRONT 25.00 REAR 15.00 SIDE 10.00

NO. EX.D.U. 0 FLOOD ZONE X DEVELOPMENT PERMIT NO. _____

PARCEL ID 11-4S-16-02911-313 SUBDIVISION MAY-FAIR

LOT 13 BLOCK _____ PHASE _____ UNIT 3 TOTAL ACRES 0.51

00000 R282811523

Culvert Permit No. 18"X32'MITERED Culvert Waiver 08-0325 Contractor's License Number BLK Applicant/Owner/Contractor HD N

Driveway Connection _____ Septic Tank Number _____ LU & Zoning checked by _____ Approved for Issuance _____ New Resident _____

COMMENTS: ELEVATION CONFIRMATION LETTER REQUIRED @ SLAB. MFE @ 164.' PER PLAT.

Check # or Cash 5028

FOR BUILDING & ZONING DEPARTMENT ONLY

(footer/Slab)

Temporary Power _____ Foundation _____ Monolithic _____
date/app. by _____ date/app. by _____ date/app. by _____

Under slab rough-in plumbing _____ Slab _____ Sheathing/Nailing _____
date/app. by _____ date/app. by _____ date/app. by _____

Framing _____ Insulation _____
date/app. by _____ date/app. by _____

Rough-in plumbing above slab and below wood floor _____ Electrical rough-in _____
date/app. by _____ date/app. by _____

Heat & Air Duct _____ Peri. beam (Lintel) _____ Pool _____
date/app. by _____ date/app. by _____ date/app. by _____

Permanent power _____ C.O. Final _____ Culvert _____
date/app. by _____ date/app. by _____ date/app. by _____

Pump pole _____ Utility Pole _____ M/H tie downs, blocking, electricity and plumbing _____
date/app. by _____ date/app. by _____ date/app. by _____

Reconnection _____ RV _____ Re-roof _____
date/app. by _____ date/app. by _____ date/app. by _____

BUILDING PERMIT FEE \$ 580.00 CERTIFICATION FEE \$ 11.56 SURCHARGE FEE \$ 11.56

MISC. FEES \$ 0.00 ZONING CERT. FEE \$ 50.00 FIRE FEE \$ 0.00 WASTE FEE \$ _____

FLOOD DEVELOPMENT FEE \$ _____ FLOOD ZONE FEE \$ 25.00 CULVERT FEE \$ _____ TOTAL FEE 678.12

INSPECTORS OFFICE _____ CLERKS OFFICE _____

NOTICE: IN ADDITION TO THE REQUIREMENTS OF THIS PERMIT, THERE MAY BE ADDITIONAL RESTRICTIONS APPLICABLE TO THIS PROPERTY THAT MAY BE FOUND IN THE PUBLIC RECORDS OF THIS COUNTY. AND THERE MAY BE ADDITIONAL PERMITS REQUIRED FROM OTHER GOVERNMENTAL ENTITIES SUCH AS WATER MANAGEMENT DISTRICTS, STATE AGENCIES, OR FEDERAL AGENCIES.

"WARNING TO OWNER: YOUR FAILURE TO RECORD A NOTICE OF COMMENCEMENT MAY RESULT IN YOUR PAYING TWICE FOR IMPROVEMENTS TO YOUR PROPERTY. IF YOU INTEND TO OBTAIN FINANCING, CONSULT WITH YOUR LENDER OR AN ATTORNEY BEFORE RECORDING YOUR NOTICE OF COMMENCEMENT."

EVERY PERMIT ISSUED SHALL BECOME INVALID UNLESS THE WORK AUTHORIZED BY SUCH PERMIT IS COMMENCED WITHIN 180 DAYS AFTER ITS ISSUANCE, OR IF THE WORK AUTHORIZED BY SUCH PERMIT IS SUSPENDED OR ABANDONED FOR A PERIOD OF 180 DAYS AFTER THE TIME THE WORK IS COMMENCED. A VALID PERMIT RECIEVES AN APPROVED INSPECTION EVERY 180 DAYS. WORK SHALL BE CONSIDERED NOT SUSPENDED, ABANDONED OR INVALID WHEN THE PERMIT HAS RECIEVED AN APPROVED INSPECTION WITHIN 180 DAYS OT THE PREVIOUS INSPECTION.

The Issuance of this Permit Does Not Waive Compliance by Permittee with Deed Restrictions.

Columbia County Building Permit Application

For Office Use Only Application # 0906-51 Date Received 6/25 By JW Permit # 1735/27921
 Zoning Official B2K Date 01.07.07 Flood Zone X Land Use Res. Low Den. Zoning RSF-2
 FEMA Map # N/A Elevation N/A MFE 164' ft River N/A Plans Examiner HO Date 6-30-0
 Comments Elevation Confirmation Letter Required at Slab

☐ NOC ☒ EH ☐ Deed or PA ☒ Site Plan ☐ State Road Info ☐ Parent Parcel # _____
☐ Dev Permit # _____ ☐ In Floodway ☐ Letter of Auth. from Contractor ☐ F W Comp. letter
 IMPACT FEES: EMS _____ Fire _____ Corr _____ Road/Code _____
 School _____ = TOTAL Suspended

Septic Permit No. 08-0325 Fax 754-9601
 Name Authorized Person Signing Permit Trent Gieberg Phone 397-0545
 Address 697 SE Holly Terrace Lake City FL 32025
 Owners Name Pete Gieberg Phone 752-7968
 911 Address 170 SW Vann Court, L.P. FL 32024
 Contractors Name Trent Gieberg Construction Inc Phone 397-0545
 Address 697 SE Holly Terrace Lake City FL 32025
 Fee Simple Owner Name & Address Pete Gieberg
 Bonding Co. Name & Address _____
 Architect/Engineer Name & Address Freeman Design
 Mortgage Lenders Name & Address _____

Circle the correct power company - FL Power & Light - Clay Elec. Suwannee Valley Elec. - Progress Energy
 Property ID Number 11-45-16-02911-313 Estimated Cost of Construction 100,000
 Subdivision Name Mayfair Unit 3 Lot 13 Block — Unit 3 Phase —
 Driving Directions 247 South Right on Mayfair Lane
Right on Vann Court 3rd on left
 Number of Existing Dwellings on Property 0

Construction of Wood Frame on concrete floor Total Acreage _____ Lot Size .51
 Do you need a Culvert Permit or Culvert Waiver or Have an Existing Drive Total Building Height 17'6"
 Actual Distance of Structure from Property Lines - Front 27 Side 34'8" Side 33'10" Rear 90'8"
 Number of Stories 1 Heated Floor Area 1608 Total Floor Area 2312 Roof Pitch 6/12

Application is hereby made to obtain a permit to do work and installations as indicated. I certify that no work or installation has commenced prior to the issuance of a permit and that all work be performed to meet the standards of all laws regulating construction in this jurisdiction.

CK # 5028

The called went 7:10 PM 6/25/09

TIME LIMITATIONS OF APPLICATION : An application for a permit for any proposed work shall be deemed to have been abandoned 180 days after the date of filing, unless such application has been pursued in good faith or a permit has been issued; except that the building official is authorized to grant one or more extensions of time for additional periods not exceeding 90 days each. The extension shall be requested in writing and justifiable cause demonstrated.

TIME LIMITATIONS OF PERMITS: Every permit issued shall become invalid unless the work authorized by such permit is commenced within 180 days after its issuance, or if the work authorized by such permit is suspended or abandoned for a period of 180 days after the time work is commenced. A valid permit receives an approved inspection every 180 days. Work shall be considered not suspended, abandoned or invalid when the permit has received an approved inspection within 180 days of the previous approved inspection.

FLORIDA'S CONSTRUCTION LIEN LAW: Protect Yourself and Your Investment: According to Florida Law, those who work on your property or provide materials, and are not paid-in-full, have a right to enforce their claim for payment against your property. This claim is known as a construction lien. If your contractor fails to pay subcontractors or material suppliers or neglects to make other legally required payments, the people who are owed money may look to your property for payment, even if you have paid your contractor in full. This means if a lien is filed against your property, it could be sold against your will to pay for labor, materials or other services which your contractor may have failed to pay.

NOTICE OF RESPONSIBILITY TO BUILDING PERMITEE: YOU ARE HEREBY NOTIFIED as the recipient of a building permit from Columbia County, Florida, you will be held responsible to the County for any damage to sidewalks and/or road curbs and gutters, concrete features and structures, together with damage to drainage facilities, removal of sod, major changes to lot grades that result in ponding of water, or other damage to roadway and other public infrastructure facilities caused by you or your contractor, subcontractors, agents or representatives in the construction and/or improvement of the building and lot for which this permit is issued. No certificate of occupancy will be issued until all corrective work to these public infrastructures and facilities has been corrected.

WARNING TO OWNER: YOUR FAILURE TO RECORD A NOTICE OF COMMENCEMENT MAY RESULT IN YOU PAYING TWICE FOR IMPROVEMENTS TO YOUR PROPERTY. A NOTICE OF COMMENCEMENT MUST BE RECORDED AND POSTED ON THE JOB SITE BEFORE THE FIRST INSPECTION. IF YOU INTEND TO OBTAIN FINANCING, CONSULT WITH YOUR LENDER OR ATTORNEY BEFORE RECORDING YOUR NOTICE OF COMMENCEMENT.

OWNERS CERTIFICATION: I hereby certify that all the foregoing information is accurate and all work will be done in compliance with all applicable laws and regulating construction and zoning. I further understand the above written responsibilities in Columbia County for obtaining this Building Permit.

Peter W. G.
Owners Signature

CONTRACTORS AFFIDAVIT: By my signature I understand and agree that I have informed and provided this written statement to the owner of all the above written responsibilities in Columbia County for obtaining this Building Permit including all application and permit time limitations.


Jeff G.
Contractor's Signature (Permitee)

Contractor's License Number RR282811523
Columbia County
Competency Card Number 000141

Affirmed under penalty of perjury to by the Contractor and subscribed before me this 25th day of June 2009.
Personally known X or Produced Identification _____

Elaine K. Tolar
State of Florida Notary Signature (For the Contractor)

SEAL:



Prepared by:
Peter W. Giebeig
PO Box 1384
Lake City, FL 32056

Inst:200812008356 Date:4/29/2008 Time:3:59 PM
Doc Stamp-Deed:364.00
DC,P DeWitt Casson, Columbia County Page 1 of 1 B:1149 P:363

CORPORATE WARRANTY DEED

THIS INDENTURE, Made the 29th of April, 2008, by
Concept Construction of North Florida, Inc. a Florida Corporation
A corporation existing under the laws of the State of Florida and having its principal place of business at:
2109 W US Highway 90, Suite 170-144, Lake City, FL 32055,
hereinafter called the Grantor,

To:
Peter W. Giebeig,
whose post office address is : P.O. Box 1384, Lake City, FL 32056
hereinafter called the Grantee:

(Wherever used herein the terms "grantor" and "grantee" include all the parties to this instrument and the heirs, legal representatives ad assigns of individuals, and the successors and assigns of corporation)

WITNESSETH: That the grantor, for and in consideration of the sum of \$10.00 and other valuable considerations, receipt whereof is hereby acknowledged, hereby grants, bargains, sells, aliens, remises, releases, conveys and confirms unto the grantee, all that certain land situate in Columbia County, Florida, viz: Tax ID# R02911-313

Lot 13, May-Fair Unit 3, a subdivision according to the plat thereof filed in Plat Book 8, Pages 84-85, of the Public Records of Columbia County, Florida.

This is an absolute conveyance of the title in consideration of the cancellation of the debt secured by the mortgage recorded in Official Records Book 1085, Page 740, of the Public Records of Columbia County, Florida, and is not intended to be an additional security.

TOGETHER, with all the tenements, hereditaments and appurtenances thereto belonging or in anywise appertaining.

TO HAVE AND TO HOLD, the same in fee simple forever.

AND the grantor hereby covenants with said grantee that the grantor is lawfully seized of said land in fee simple; that the grantor has good right and lawful authority to sell and convey said land, and hereby warrants the title to said land and will defend the same against the lawful claims of all persons claiming by, through or under the said grantor.

IN WITNESS WHEREOF, the said grantor has hereunto set their hand and seal the day and year first above written.

Signed, sealed and delivered in our presence:

Donna Cox
Witness Donna Cox
Traci Landry
Witness TRACI LANDRY

Concept Construction of North Florida, Inc.

BY: Brian S. Crawford
Brian S. Crawford, President

STATE OF FLORIDA
COUNTY OF COLUMBIA

I HEREBY CERTIFY that on this day, before me, an officer duly authorized in the State aforesaid and in the county aforesaid, to take acknowledgments, personally appeared Brian S. Crawford, well known to be the PRESIDENT, respectively of Concept Construction of North Florida, Inc., a Florida Corporation named as grantor in the foregoing deed, and that they severally acknowledged executing the same in the presence of two subscribing witnesses freely and voluntarily under authority duly vested.

WITNESS my hand and official seal in the County and State last aforesaid this 29th day of April, 2008.

Donna Cox
NOTARY PUBLIC

My Commission expires:



DONNA COX
Notary Public, State of Florida
My Comm. Expires Jan. 16, 2010
Comm. No. DD 507061
Bonded Thru Notary Public Underwriters



Columbia County Tax Collector

Site Provided by...
governmax.com T1.11

Tax Record

```
print
```

Account Number
1 of 1

Last Update: 6/25/2009 10:47:28 AM EDT

Details

Tax Record

» [Print View](#)

Legal Desc.

Appraiser Data

Tax Payment

Payment History

Print Tax Bill NEW!

Searches

Account Number

GEO Number

Owner Name

Property Address

Certificate **NEW!**

Mailing Address

Site Functions

Disclaimer

Tax Search

Local Business Tax

Tax Sale List

[Contact Us](#)

County Login

Home

Ad Valorem Taxes and Non-Ad Valorem Assessments

The information contained herein does not constitute a title search and should not be relied on as such.

Account Number		Tax Type		Tax Year	
R02911-313		REAL ESTATE		2008	
Mailing Address			Property Address		
GIEBEIG PETER W P O BOX 1384 LAKE CITY FL 32056			170 VANN CT SW		
			GEO Number 164S11-02911-313		
Assessed Value		Exempt Amount		Taxable Value	
\$38,000.00		See Below		See Below	
Exemption Detail		Millage Code		Escrow Code	
NO EXEMPTIONS		002			
Legal Description (click for full description)					
11-4S-16 0000/0000 .51 Acres LOT 13 MAY-FAIR S/D UNIT 3. WD 1085-739, WD 1149-363					
Ad Valorem Taxes					
Taxing Authority	Rate	Exemption Amount	Taxable Value	Taxes Levied	
BOARD OF COUNTY COMMISSIONERS	7.8910	0	\$38,000	\$299.86	
COLUMBIA COUNTY SCHOOL BOARD					
DISCRETIONARY	0.7480	0	\$38,000	\$28.42	
LOCAL	5.2220	0	\$38,000	\$198.44	
CAPITAL OUTLAY	1.7500	0	\$38,000	\$66.50	
SUWANNEE RIVER WATER MGT DIST	0.4399	0	\$38,000	\$16.72	
LAKE SHORE HOSPITAL AUTHORITY	2.0160	0	\$38,000	\$76.61	
COLUMBIA COUNTY INDUSTRIAL	0.1240	0	\$38,000	\$4.71	
Total Millage		18.1909	Total Taxes		\$691.26
Non-Ad Valorem Assessments					
Code	Levying Authority				Amount
FFIR	FIRE ASSESSMENTS				\$69.58
Total Assessments					\$69.58
Taxes & Assessments					\$760.84
If Paid By					Amount Due
					\$0.00

Date Paid	Transaction	Receipt	Item	Amount Paid
3/30/2009	PAYMENT	2604126.0026	2008	\$760.84

Prior Years Payment History

Prior Year Taxes Due
NO DELINQUENT TAXES

FLORIDA ENERGY EFFICIENCY CODE FOR BUILDING CONSTRUCTION**Florida Department of Community Affairs Residential Performance Method A**

Project Name: Mayfair Lot 13 St Johns Model
 Street:
 City, State, Zip: Lake City, FL, 32055-
 Owner:
 Design Location: FL, Gainesville

Builder Name: T. Geibeig
 Permit Office:
 Permit Number:
 Jurisdiction:

1. New construction or existing New (From Plans)
 2. Single family or multiple family Single-family
 3. Number of units, if multiple family 1
 4. Number of Bedrooms 3
 5. Is this a worst case? No
 6. Conditioned floor area (ft²) 1608

7. Windows	Description	Area
a. U-Factor:	Sgl, U=1.20	78.00 ft ²
SHGC:	SHGC=0.70	
b. U-Factor:	Sgl, U=0.55	30.00 ft ²
SHGC:	SHGC=0.60	
c. U-Factor:	N/A	ft ²
SHGC:		
d. U-Factor:	N/A	ft ²
SHGC:		
e. U-Factor:	N/A	ft ²
SHGC:		

8. Floor Types	Insulation	Area
a. Slab-On-Grade Edge Insulation	R=0.0	1608.00 ft ²
b. N/A	R=	ft ²
c. N/A	R=	ft ²

9. Wall Types	Insulation	Area
a. Frame - Wood, Exterior	R=13.0	1164.00 ft ²
b. Frame - Wood, Adjacent	R=13.0	160.00 ft ²
c. N/A	R=	ft ²
d. N/A	R=	ft ²

10. Ceiling Types	Insulation	Area
a. Under Attic (Vented)	R=30.0	1608.00 ft ²
b. N/A	R=	ft ²
c. N/A	R=	ft ²

11. Ducts
 a. Sup: Attic Ret: Attic AH: Interior Sup. R= 6, 321.6 ft²

12. Cooling systems
 a. Central Unit
 Cap: 36 kBtu/hr
 SEER: 14

13. Heating systems
 a. Electric Heat Pump
 Cap: 36 kBtu/hr
 HSPF: 7.7

14. Hot water systems
 a. Electric
 Cap: 50 gallons
 EF: 0.92

b. Conservation features
 None

15. Credits Pstat

Glass/Floor Area: 0.067

Total As-Built Modified Loads: 27.88

Total Baseline Loads: 34.16

PASS

I hereby certify that the plans and specifications covered by this calculation are in compliance with the Florida Energy Code.

PREPARED BY: Debbie Motes
 DATE: 6-11-09

I hereby certify that this building, as designed, is in compliance with the Florida Energy Code.

OWNER/AGENT: _____
 DATE: _____

Review of the plans and specifications covered by this calculation indicates compliance with the Florida Energy Code. Before construction is completed this building will be inspected for compliance with Section 553.908 Florida Statutes.



BUILDING OFFICIAL: _____
 DATE: _____

- Compliance requires certification by the air handler unit manufacturer that the air handler enclosure qualifies as certified factory-sealed in accordance with N1110.A.3.

PROJECT

Title: Mayfair Lot 13 St Johns Model	Bedrooms: 3	Address Type: Street Address
Building Type: FLAsBuilt	Bathrooms: 0	Lot #
Owner:	Conditioned Area: 1608	SubDivision:
# of Units: 1	Total Stories: 1	PlatBook:
Builder Name: T. Geibeig	Worst Case: No	Street:
Permit Office:	Rotate Angle: 0	County: Columbia
Jurisdiction:	Cross Ventilation:	City, State, Zip: Lake City ,
Family Type: Single-family	Whole House Fan:	FI , 32055-
New/Existing: New (From Plans)		
Comment:		

CLIMATE

✓	Design Location	TMY Site	IECC Zone	Design Temp 97.5 %	Design Temp 2.5 %	Int Design Temp Winter	Int Design Temp Summer	Heating Degree Days	Design Moisture	Daily Temp Range
✓	FL, Gainesville	FL_GAINESVILLE_REGI	2	32	92	75	70	1305.5	51	Medium

FLOORS

✓	#	Floor Type	Perimeter	R-Value	Area	Tile	Wood	Carpet
✓	1	Slab-On-Grade Edge Insulatio	206 ft	0	1608 ft²	0.2	0.2	0.6

ROOF

✓	#	Type	Materials	Roof Area	Gable Area	Roof Color	Solar Absor.	Tested	Deck Insul.	Pitch
✓	1	Hip	Composition shingles	1798 ft²	0 ft²	Medium	0.96	No	0	26.6 deg

ATTIC

✓	#	Type	Ventilation	Vent Ratio (1 in)	Area	RBS	IRCC
✓	1	Full attic	Vented	300	1608 ft²	N	N

CEILING

✓	#	Ceiling Type	R-Value	Area	Framing Frac	Truss Type
✓	1	Under Attic (Vented)	30	1608 ft²	0.11	Wood

WALLS

✓	#	Ornt	Adjacent To	Wall Type	Cavity R-Value	Area	Sheathing R-Value	Framing Fraction	Solar Absor.
✓	1	E	Exterior	Frame - Wood	13	421.33 ft²		0.23	0.75
✓	2	N	Exterior	Frame - Wood	13	240.67 ft²		0.23	0.75
✓	3	W	Exterior	Frame - Wood	13	261.33 ft²		0.23	0.75
✓	4	S	Exterior	Frame - Wood	13	240.67 ft²		0.23	0.75
✓	5	W	Garage	Frame - Wood	13	160 ft²		0.23	0.01

DOORS

✓	#	Ornt	Door Type	Storms	U-Value	Area
✓	1	E	Insulated	None	0.46	40 ft²
✓	2	W	Insulated	None	0.46	33.33 ft²

WINDOWS

Window orientation below is as entered. Actual orientation is modified by rotate angle shown in "Project" section above.

✓	#	Ornt	Frame	Panes	NFRC	U-Factor	SHGC	Storms	Area	Overhang		Int Shade	Screening
										Depth	Separation		
✓	1	E	Metal	Single (Tinted)	Yes	0.55	0.6	N	30 ft²	1 ft 6 in	1 ft 6 in	HERS 2006	None
✓	2	E	Metal	Single (Tinted)	Yes	1.2	0.7	N	20 ft²	1 ft 6 in	1 ft 6 in	HERS 2006	None
✓	3	N	Metal	Single (Tinted)	Yes	1.2	0.7	N	5 ft²	1 ft 6 in	1 ft 6 in	HERS 2006	None
✓	4	N	Metal	Single (Tinted)	Yes	1.2	0.7	N	8 ft²	1 ft 6 in	1 ft 6 in	HERS 2006	None
✓	5	W	Metal	Single (Tinted)	Yes	1.2	0.7	N	20 ft²	1 ft 6 in	1 ft 6 in	HERS 2006	None
✓	6	W	Metal	Single (Tinted)	Yes	1.2	0.7	N	25 ft²	1 ft 6 in	1 ft 6 in	HERS 2006	None

INFILTRATION & VENTING

✓	Method	SLA	CFM 50	ACH 50	ELA	EqLA	--- Forced Ventilation ---		Run Time	Fan
							Supply CFM	Exhaust CFM	Fraction	Watts
✓	Default	0.00036	1518	7.08	83.4	156.8	0 cfm	0 cfm	0	0

GARAGE

✓	#	Floor Area	Ceiling Area	Exposed Wall Perimeter	Avg. Wall Height	Exposed Wall Insulation
✓	1	400 ft²	400 ft²	64 ft	8 ft	11

COOLING SYSTEM

✓	#	System Type	Subtype	Efficiency	Capacity	Air Flow	SHR	Ductless
✓	1	Central Unit	None	SEER: 14	36 kBtu/hr	1080 cfm	0.75	False

HEATING SYSTEM

✓	#	System Type	Subtype	Efficiency	Capacity	Ductless
✓	1	Electric Heat Pump	None	HSPF: 7.7	36 kBtu/hr	False

HOT WATER SYSTEM

✓	#	System Type	EF	Cap	Use	SetPnt	Conservation
✓	1	Electric	0.92	50 gal	60 gal	120 deg	None

SOLAR HOT WATER SYSTEM

✓	FSEC	Company Name	System Model #	Collector Model #	Collector Area	Storage Volume	FEF
	Cert #						
✓	None	None			ft²		

DUCTS

✓	#	--- Supply ---		--- Return ---		Leakage Type	Air Handler	CFM 25	Percent Leakage	QN	RLF
		Location	R-Value	Area	Location	Area					
	1	Attic	6	321.6 ft	Attic	80.4 ft ²	Default Leakage	Interior			

TEMPERATURES

Programable Thermostat: Y						Ceiling Fans:							
Cooling	<input checked="" type="checkbox"/> Jan	<input checked="" type="checkbox"/> Feb	<input checked="" type="checkbox"/> Mar	<input checked="" type="checkbox"/> Apr	<input checked="" type="checkbox"/> May	<input checked="" type="checkbox"/> Jun	<input checked="" type="checkbox"/> Jul	<input checked="" type="checkbox"/> Aug	<input checked="" type="checkbox"/> Sep	<input checked="" type="checkbox"/> Oct	<input checked="" type="checkbox"/> Nov	<input checked="" type="checkbox"/> Dec	
Heating	<input checked="" type="checkbox"/> Jan	<input checked="" type="checkbox"/> Feb	<input checked="" type="checkbox"/> Mar	<input checked="" type="checkbox"/> Apr	<input checked="" type="checkbox"/> May	<input checked="" type="checkbox"/> Jun	<input checked="" type="checkbox"/> Jul	<input checked="" type="checkbox"/> Aug	<input checked="" type="checkbox"/> Sep	<input checked="" type="checkbox"/> Oct	<input checked="" type="checkbox"/> Nov	<input checked="" type="checkbox"/> Dec	
Venting	<input checked="" type="checkbox"/> Jan	<input checked="" type="checkbox"/> Feb	<input checked="" type="checkbox"/> Mar	<input checked="" type="checkbox"/> Apr	<input checked="" type="checkbox"/> May	<input checked="" type="checkbox"/> Jun	<input checked="" type="checkbox"/> Jul	<input checked="" type="checkbox"/> Aug	<input checked="" type="checkbox"/> Sep	<input checked="" type="checkbox"/> Oct	<input checked="" type="checkbox"/> Nov	<input checked="" type="checkbox"/> Dec	
Thermostat Schedule: HERS 2006 Reference													
Schedule Type		1	2	3	4	5	6	7	8	9	10	11	12
Cooling (WD)	AM	78	78	78	78	78	78	78	78	80	80	80	80
	PM	80	80	78	78	78	78	78	78	78	78	78	78
Cooling (WEH)	AM	78	78	78	78	78	78	78	78	78	78	78	78
	PM	78	78	78	78	78	78	78	78	78	78	78	78
Heating (WD)	AM	66	66	66	66	66	68	68	68	68	68	68	68
	PM	68	68	68	68	68	68	68	68	68	68	66	66
Heating (WEH)	AM	66	66	66	66	66	68	68	68	68	68	68	68
	PM	68	68	68	68	68	68	68	68	68	68	66	66

Code Compliance Checklist

Residential Whole Building Performance Method A - Details

ADDRESS:

Lake City, Fl, 32055-

PERMIT #:

INFILTRATION REDUCTION COMPLIANCE CHECKLIST

COMPONENTS	SECTION	REQUIREMENTS FOR EACH PRACTICE	CHECK
Exterior Windows & Doors	N1106.AB.1.1	Maximum: .3 cfm/sq.ft. window area; .5 cfm/sq.ft. door area.	
Exterior & Adjacent Walls	N1106.AB.1.2.1	Caulk, gasket, weatherstrip or seal between: windows/doors & frames, surrounding wall; foundation & wall sole or sill plate; joints between exterior wall panels at corners; utility penetrations; between wall panels & top/bottom plates; between walls and floor. EXCEPTION: Frame walls where a continuous infiltration barrier is installed that extends from, and is sealed to, the foundation to the top plate.	
Floors	N1106.AB.1.2.2	Penetrations/openings > 1/8" sealed unless backed by truss or joint members. EXCEPTION: Frame floors where a continuous infiltration barrier is installed that is sealed to the perimeter, penetrations and seams.	
Ceilings	N1106.AB.1.2.3	Between walls & ceilings; penetrations of ceiling plane to top floor; around shafts, chases, soffits, chimneys, cabinets sealed to continuous air barrier; gaps in gyp board & top plate; attic access. EXCEPTION: Frame ceilings where a continuous infiltration barrier is installed that is sealed at the perimeter, at penetrations and seams.	
Recessed Lighting Fixtures	N1106.AB.1.2.4	Type IC rated with no penetrations, sealed; or Type IC or non-IC rated, installed inside a sealed box with 1/2" clearance & 3" from insulation; or Type IC with < 2.0 cfm from conditioned space, tested.	
Multi-story Houses	N1106.AB.1.2.5	Air barrier on perimeter of floor cavity between floors.	
Additional Infiltration reqts	N1106.AB.1.3	Exhaust fans vented to outdoors, dampers; combustion space heaters comply with NFPA, have combustion air.	

OTHER PRESCRIPTIVE MEASURES (must be met or exceeded by all residences.)

COMPONENTS	SECTION	REQUIREMENTS	CHECK
Water Heaters	N1112.AB.3	Comply with efficiency requirements in Table N112.ABC.3. Switch or clearly marked circuit breaker (electric) or cutoff (gas) must be provided. External or built-in heat trap required.	
Swimming Pools & Spas	N1112.AB.2.3	Spas & heated pools must have covers (except solar heated). Non-commercial pools must have a pump timer. Gas spa & pool heaters must have a minimum thermal efficiency of 78%. Heat pump pool heaters shall have a minimum COP of 4.0.	
Shower heads	N1112.AB.2.4	Water flow must be restricted to no more than 2.5 gallons per minute at 80 PSIG.	
Air Distribution Systems	N1110.AB	All ducts, fittings, mechanical equipment and plenum chambers shall be mechanically attached, sealed, insulated and installed in accordance with the criteria of Section N1110.AB. Ducts in unconditioned attics: R-6 min. insulation.	
HVAC Controls	N1107.AB.2	Separate readily accessible manual or automatic thermostat for each system.	
Insulation	N1104.AB.1 N1102.B.1.1	Ceilings-Min. R-19. Common walls-frame R-11 or CBS R-3 both sides. Common ceiling & floors R-11.	

ENERGY PERFORMANCE LEVEL (EPL) DISPLAY CARD

ESTIMATED ENERGY PERFORMANCE INDEX* = 82

The lower the EnergyPerformance Index, the more efficient the home.

1. New construction or existing	New (From Plans)	9. Wall Types	Insulation	Area
2. Single family or multiple family	Single-family	a. Frame - Wood, Exterior	R=13.0	1164.00 ft ²
3. Number of units, if multiple family	1	b. Frame - Wood, Adjacent	R=13.0	160.00 ft ²
4. Number of Bedrooms	3	c. N/A	R=	ft ²
5. Is this a worst case?	No	d. N/A	R=	ft ²
6. Conditioned floor area (ft ²)	1608	10. Ceiling Types	Insulation	Area
7. Windows**	Description	a. Under Attic (Vented)	R=30.0	1608.00 ft ²
a. U-Factor:	Sgl, U=1.20	b. N/A	R=	ft ²
SHGC:	SHGC=0.70	c. N/A	R=	ft ²
b. U-Factor:	Sgl, U=0.55	11. Ducts		
SHGC:	SHGC=0.60	a. Sup: Attic Ret: Attic AH: Interior Sup. R= 6, 321.6 ft ²		
c. U-Factor:	N/A	12. Cooling systems		
SHGC:		a. Central Unit	Cap: 36 kBtu/hr	
d. U-Factor:	N/A		SEER: 14	
SHGC:		13. Heating systems		
e. U-Factor:	N/A	a. Electric Heat Pump	Cap: 36 kBtu/hr	
SHGC:			HSPF: 7.7	
8. Floor Types	Insulation	14. Hot water systems		
a. Slab-On-Grade Edge Insulation	R=0.0	a. Electric	Cap: 50 gallons	
b. N/A	R=		EF: 0.92	
c. N/A	R=	b. Conservation features		
		None		
		15. Credits		Pstat

I certify that this home has complied with the Florida Energy Efficiency Code for Building Construction through the above energy saving features which will be installed (or exceeded) in this home before final inspection. Otherwise, a new EPL Display Card will be completed based on installed Code compliant features.

Builder Signature: _____ Date: _____

Address of New Home: _____ City/FL Zip: _____



*Note: The home's estimated Energy Performance Index is only available through the EnergyGauge USA - FlaRes2008 computer program. This is not a Building Energy Rating. If your Index is below 100, your home may qualify for incentives if you obtain a Florida Energy Gauge Rating. Contact the Energy Gauge Hotline at (321) 638-1492 or see the Energy Gauge web site at energygauge.com for information and a list of certified Raters. For information about Florida's Energy Efficiency Code for Building Construction, contact the Department of Community Affairs at (850) 487-1824.

**Label required by Section 13-104.4.5 of the Florida Building Code, Building, or Section B2.1.1 of Appendix G of the Florida Building Code, Residential, if not DEFAULT.

PRODUCT APPROVAL SPECIFICATION SHEET

Location: SW Van Court

Project Name: Lot #13 - Mayfair


As required by Florida Statute 553.842 and Florida Administrative Code 9B-72, please provide the information and the product approval number(s) on the building components listed below if they will be utilized on the construction project for which you are applying for a building permit on or after April 1, 2004. We recommend you contact your local product supplier should you not know the product approval number for any of the applicable listed products. More information about statewide product approval can be obtained at


Category/Subcategory	Manufacturer	Product Description	Approval Number(s)
A. EXTERIOR DOORS			
1. Swinging	Therma-Tru	6'8 Door	NOA 01-0828.08
2. Sliding	Mi Home	Alum. Sliding glass	03-1224.01
3. Sectional	Clopay	Sectional P6	05-1212.02
4. Roll up			
5. Automatic			
6. Other			
B. WINDOWS			
1. Single hung	Mi Home	Alum SH window	03-1245.02
2. Horizontal Slider			
3. Casement			
4. Double Hung			
5. Fixed			
6. Awning			
7. Pass-through			
8. Projected			
9. Mullion			
10. Wind Breaker			
11. Dual Action			
12. Other			
C. PANEL WALL			
1. Siding			
2. Soffits			
3. EIFS			
4. Storefronts			
5. Curtain walls			
6. Wall louver			
7. Glass block			
8. Membrane			
9. Greenhouse			
10. Other			
D. ROOFING PRODUCTS			
1. Asphalt Shingles	Tamko	Roof	03-0620.01
2. Underlayments			
3. Roofing Fasteners			
4. Non-structural Metal Rf			
5. Built-Up Roofing			
6. Modified Bitumen			
7. Single Ply Roofing Sys			
8. Roofing Tiles			
9. Roofing Insulation			
10. Waterproofing			
11. Wood shingles /shakes			
12. Roofing Slate			

Category/Subcategory (cont.)	Manufacturer	Product Description	Approval Number(s)
13. Liquid Applied Roof Sys			
14. Cements-Adhesives – Coatings			
15. Roof Tile Adhesive			
16. Spray Applied Polyurethane Roof			
17. Other			
E. SHUTTERS			
1. Accordion			
2. Bahama			
3. Storm Panels			
4. Colonial			
5. Roll-up			
6. Equipment			
7. Others			
F. SKYLIGHTS			
1. Skylight			
2. Other			
G. STRUCTURAL COMPONENTS			
1. Wood connector/anchor			
2. Truss plates			
3. Engineered lumber			
4. Railing			
5. Coolers-freezers			
6. Concrete Admixtures			
7. Material			
8. Insulation Forms			
9. Plastics			
10. Deck-Roof			
11. Wall			
12. Sheds			
13. Other			
H. NEW EXTERIOR ENVELOPE PRODUCTS			
1.			
2.			

The products listed below did not demonstrate product approval at plan review. I understand that at the time of inspection of these products, the following information must be available to the inspector on the jobsite; 1) copy of the product approval, 2) the performance characteristics which the product was tested and certified to comply with, 3) copy of the applicable manufacturers installation requirements.

I understand these products may have to be removed if approval cannot be demonstrated during inspection


 Contractor or Contractor's Authorized Agent Signature


 Print Name Date

 Location

 Permit # (FOR STAFF USE ONLY)



STATE OF FLORIDA
DEPARTMENT OF HEALTH

APPLICATION FOR ONSITE SEWAGE DISPOSAL SYSTEM CONSTRUCTION PERMIT


Permit Application Number

Good for 18 months

08-0325

PART II - SITE PLAN

Scale: Each block represents 5 feet and 1 inch = 50 feet.



Notes: LOT 13 MAYFAIR PH 3

11-45-16-02911-313

Pete Gierbeig (CONCEPT CONSTR.)

Site Plan submitted by:

Pete Gierbeig
Signature

Ag...
Title

Plan Approved ☒

Not Approved ☐

Date 7-28-08

By

Mn O Zm

Columbia

County Health Department

ALL CHANGES MUST BE APPROVED BY THE COUNTY HEALTH DEPARTMENT

Nov. 06 07 12:04p

Lynch Well Drilling

386-752-1477

p.2

Water, Wells
Pumps & Service

Phone: (386) 752-6677
Fax: (386) 752-1477

Lynch Well Drilling, Inc.

173 SW Young Place
Lake City, FL 32025
www.lynchwelldrilling.com

November 6, 2007

To Whom It May Concern:

As required by building code regulations for Columbia County in order that a building permit can be issued, the following well information is provided with regard to the above-referenced well:

Size of Pump Motor:	1 Horse Power
Size of Pressure Tank:	81-Gallon Bladder Tank
Cycle Stop Valve Used:	No

Should you require any additional information, please contact us.

Sincerely,



Linda Newcomb
Lynch Well Drilling, Inc.

Columbia County Building Department Culvert Permit

Culvert Permit No.
000001734

DATE 07/01/2009 PARCEL ID # 11-4S-16-02911-316

APPLICANT B. TRENT GIEBEIG

PHONE 386.397.0545

ADDRESS 697 SE HOLLY TERRACE

LAKE CITY

FL 32025

OWNER PETE GIEBEIG

PHONE 386.752.7968

ADDRESS 123 SW LUCILLE CT

LAKE CITY

FL 32024

CONTRACTOR B. TRENT GIEBEIG

PHONE 386.752.7968

LOCATION OF PROPERTY 90-W TO SR.247-S,TL TO SW MAY-FAIR LN,TR TO LUCILLE CT,TR

1ST LOT ON R.

SUBDIVISION/LOT/BLOCK/PHASE/UNIT MAY-FAIR

16

3

SIGNATURE

INSTALLATION REQUIREMENTS

☒ X

Culvert size will be 18 inches in diameter with a total length of 32 feet, leaving 24 feet of driving surface. Both ends will be mitered 4 foot with a 4 : 1 slope and poured with a 4 inch thick reinforced concrete slab.

INSTALLATION NOTE: Turnouts will be required as follows:

- a) a majority of the current and existing driveway turnouts are paved, or;
- b) the driveway to be served will be paved or formed with concrete.

Turnouts shall be concrete or paved a minimum of 12 feet wide or the width of the concrete or paved driveway, whichever is greater. The width shall conform to the current and existing paved or concreted turnouts.

☐

Culvert installation shall conform to the approved site plan standards.

☐

Department of Transportation Permit installation approved standards.

☐

Other _____

**ALL PROPER SAFETY REQUIREMENTS SHOULD BE FOLLOWED
DURING THE INSTALATION OF THE CULVERT.**

135 NE Hernando Ave., Suite B-21
Lake City, FL 32055

Phone: 386-758-1008 Fax: 386-758-2160

Amount Paid 25.00



Inst: 200912011031 Date: 7/2/2009 Time: 9:15 AM

CC: P. DeWitt Cason, Columbia County Page 1 of 1 3:1176 P:1084

NOTICE OF COMMENCEMENT

County Clerk's Office Stamp or Seal

Tax Parcel Identification Number 1-4s-16-02911-313

THE UNDERSIGNED hereby gives notice that improvements will be made to certain real property, and in accordance with Section 713.13 of the Florida Statutes, the following information is provided in this NOTICE OF COMMENCEMENT.

1. Description of property (legal description): Lot # 13 May Fair Unit III
 a) Street (job) Address: 170 SW Van Court Lake City, FL 32024
2. General description of improvements: Construction of Single Family Residence
3. Owner Information
 a) Name and address: Peter W. Gieberg P.O. Box 1384 Lake City, FL 32056
 b) Name and address of fee simple titleholder (if other than owner): _____
 c) Interest in property: Fee Simple
4. Contractor Information
 a) Name and address: Trent Gieberg Construction, Inc. 697 SE Holly Terrace
 b) Telephone No.: 386-752-0791 Fax No. (Opt.): Lake City, FL 32025
5. Surety Information
 a) Name and address: N/A
 b) Amount of Bond: _____
 c) Telephone No.: _____ Fax No. (Opt.): _____
6. Lender
 a) Name and address: N/A
 b) Phone No.: _____
7. Identity of person within the State of Florida designated by owner upon whom notices or other documents may be served:
 a) Name and address: N/A
 b) Telephone No.: _____ Fax No. (Opt.): _____
8. In addition to himself, owner designates the following person to receive a copy of the Lienor's Notice as provided in Section 713.13(1)(b), Florida Statutes:
 a) Name and address: N/A
 b) Telephone No.: _____ Fax No. (Opt.): _____
9. Expiration date of Notice of Commencement (the expiration date is one year from the date of recording unless a different date is specified): _____

WARNING TO OWNER: ANY PAYMENTS MADE BY THE OWNER AFTER THE EXPIRATION OF THE NOTICE OF COMMENCEMENT ARE CONSIDERED IMPROPER PAYMENTS UNDER CHAPTER 713, PART I, SECTION 713.13, FLORIDA STATUTES, AND CAN RESULT IN YOUR PAYING TWICE FOR IMPROVEMENTS TO YOUR PROPERTY; A NOTICE OF COMMENCEMENT MUST BE RECORDED AND POSTED ON THE JOB SITE BEFORE THE FIRST INSPECTION. IF YOU INTEND TO OBTAIN FINANCING, CONSULT YOUR LENDER OR AN ATTORNEY BEFORE COMMENCING WORK OR RECORDING YOUR NOTICE OF COMMENCEMENT.


STATE OF FLORIDA
 COUNTY OF COLUMBIA

10. Peter W. Gieberg
 Signature of Owner or Owner's Authorized Office/Director/Partner/Manager
Peter W. Gieberg
 Print Name

The foregoing instrument was acknowledged before me, a Florida Notary, this 1st day of July, 2009, by:
Peter W. Gieberg as Owner (type of authority, e.g. officer, trustee, attorney
 fact) for Peter W. Gieberg (name of party on behalf of whom instrument was executed).

Personally Known X OR Produced Identification _____ Type _____

Notary Signature Elaine K. Tolar Notary Stamp or Seal:



—AND—

11. Verification pursuant to Section 92.525, Florida Statutes. Under penalties of perjury, I declare that I have read the foregoing and that the facts stated in it are true to the best of my knowledge and belief.

Peter W. Gieberg
 Signature of Natural Person Signing (in line #10 above.)



BRITT SURVEYING & ASSOCIATES

830 West Duval Street • Lake City, FL 32055
Phone (386) 752-7163 • Fax (386) 752-5573

Land Surveyors
and Mappers

27921

07/06/09 (09/21/09 revised)

L-19971

To Whom It May Concern:

C/o: Trent Giebieg

Re: Lots 13 in May-Fair Unit 3 / 11-4S-16-02911-313

The elevation of the top of the batter boards for the residence's finished floor is 164.91 feet. The minimum finished floor elevation is 164.00 feet as per the plat of record. The highest adjacent grade is 162.8 feet. The lowest adjacent grade is 162.6 feet. The elevations shown hereon are based on NGVD 29 Datum.

L. Scott Britt
PLS #5757

O.K.
A.S. Brecken
9-21-09



**COLUMBIA COUNTY BUILDING DEPARTMENT
RESIDENTIAL CHECK LIST REQUIREMENTS**

**MINIMUM PLAN REQUIREMENTS FOR THE
FLORIDA BUILDING CODE RESIDENTIAL 2007
ONE (1) AND TWO (2) FAMILY DWELLINGS**

ALL REQUIREMENTS ARE SUBJECT TO CHANGE

ALL BUILDING PLANS MUST INDICATE COMPLIANCE with the Current 2007 FLORIDA BUILDING CODES RESIDENTIAL. ALL PLANS OR DRAWINGS SHALL PROVIDE CALCULATIONS AND DETAILS THAT HAVE THE SEAL AND SIGNATURE OF A CERTIFIED ARCHITECT OR ENGINEER REGISTERED IN THE STATE OF FLORIDA, OR ALTERNATE METHODOLOGIES, APPROVED BY THE STATE OF FLORIDA BUILDING COMMISSION FOR ONE-AND-TWO FAMILY DWELLINGS.

FOR DESIGN PURPOSES THE FOLLOWING BASIC WIND SPEEDS ARE PER FIGURE R301.2(4) of the FLORIDA BUILDING CODES RESIDENTIAL (Florida Wind speed map) SHALL BE USED.

WIND SPEED LINE SHALL BE DEFINED AS FOLLOWS: THE CENTERLINE OF INTERSTATE 75.

ALL BUILDINGS CONSTRUCTED EAST OF SAID LINE SHALL BE ----- 100 MPH
ALL BUILDINGS CONSTRUCTED WEST OF SAID LINE SHALL BE -----110 MPH
NO AREA IN COLUMBIA COUNTY IS IN A WIND BORNE DEBRIS REGION

**GENERAL REQUIREMENTS:
APPLICANT – PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL**


Items to Include-
Each Box shall be
Circled as
Applicable

			Yes	No	N/A
1	Two (2) complete sets of plans containing the following:				
2	All drawings must be clear, concise, drawn to scale, details that are not used shall be marked void				
3	Condition space (Sq. Ft.) <i>1605</i>	Total (Sq. Ft.) under roof <i>212</i>	IIIIIIII	IIIIIIII	IIII

Designers name and signature shall be on all documents and a licensed architect or engineer, signature and official embossed seal shall be affixed to the plans and documents as per the FLORIDA BUILDING CODES RESIDENTIAL R101.2.1

Site Plan information including:

4	Dimensions of lot or parcel of land		✓		
5	Dimensions of all building set backs		✓		
6	Location of all other structures (include square footage of structures) on parcel, existing or proposed well and septic tank and all utility easements.		✓		
7	Provide a full legal description of property.		✓		



Wind-load Engineering Summary, calculations and any details required

GENERAL REQUIREMENTS: APPLICANT – PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL		Items to Include- Each Box shall be Circled as Applicable		
		IIIIII	IIII	IIIIII
		YES	NO	N/A
8	Plans or specifications must show compliance with FBCR Chapter 3			
9	Basic wind speed (3-second gust), miles per hour	/		
10	(Wind exposure – if more than one wind exposure is used, the wind exposure and applicable wind direction shall be indicated)	/		
11	Wind importance factor and nature of occupancy	/		
12	The applicable internal pressure coefficient, Components and Cladding	/		
13	The design wind pressure in terms of psf (kN/m ²), to be used for the design of exterior component, cladding materials not specifically designed by the registered design professional.	/		

Elevations Drawing including:

14	All side views of the structure	/		
15	Roof pitch	/		
16	Overhang dimensions and detail with attic ventilation	/		
17	Location, size and height above roof of chimneys	/		
18	Location and size of skylights with Florida Product Approval	/		
18	Number of stories	/		
20A	Building height from the established grade to the roofs highest peak	/		

Floor Plan including:

20	Dimensioned area plan showing rooms, attached garage, breeze ways, covered porches, deck, balconies	/		
21	Raised floor surfaces located more than 30 inches above the floor or grade	/		
22	All exterior and interior shear walls indicated	/		
23	Shear wall opening shown (Windows, Doors and Garage doors)	/		
24	Emergency escape and rescue opening shown in each bedroom (net clear opening shown)	/		
25	Safety glazing of glass where needed	/		
26	Fireplaces types (gas appliance) (vented or non-vented) or wood burning with Hearth (see chapter 10 of FBCR)	/		
27	Stairs with dimensions (width, tread and riser and total run) details of guardrails, Handrails (see FBCR SECTION 311)	/		
28	Identify accessibility of bathroom (see FBCR SECTION 322)	/		

All materials placed within opening or onto/into exterior walls, soffits or roofs shall have Florida product approval number and mfg. installation information submitted with the plan (see Florida product approval form)

GENERAL REQUIREMENTS:
APPLICANT – PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL

Items to Include-
Each Box shall be
Circled as
Applicable

FBCR 403: Foundation Plans

		YES	NO	N/A
29	Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size and type of reinforcing.	1		
30	All posts and/or column footing including size and reinforcing			
31	Any special support required by soil analysis such as piling.			
32	Assumed load-bearing value of soil _____ Pound Per Square Foot			
33	Location of horizontal and vertical steel, for foundation or walls (include # size and type)			

FBCR 506: CONCRETE SLAB ON GRADE

34	Show Vapor retarder (6mil. Polyethylene with joints lapped 6 inches and sealed)	1		
35	Show control joints, synthetic fiber reinforcement or welded wire fabric reinforcement and Supports			

FBCR 320: PROTECTION AGAINST TERMITES

36	Indicate on the foundation plan if soil treatment is used for subterranean termite prevention or submit other approved termite protection methods. Protection shall be provided by registered termiticides	1		
----	---	---	--	--

FBCR 606: Masonry Walls and Stem walls (load bearing & shear Walls)

37	Show all materials making up walls, wall height, and Block size, mortar type	1		
38	Show all Lintel sizes, type, spans and tie-beam sizes and spacing of reinforcement			

Metal frame shear wall and roof systems shall be designed, signed and sealed by Florida Prof. Engineer or Architect

Floor Framing System: First and/or second story

39	Floor truss package shall including layout and details, signed and sealed by Florida Registered Professional Engineer			
40	Show conventional floor joist type, size, span, spacing and attachment to load bearing walls, stem walls and/or piers			
41	Girder type, size and spacing to load bearing walls, stem wall and/or piers			
42	Attachment of joist to girder			
43	Wind load requirements where applicable			
44	Show required under-floor crawl space			
45	Show required amount of ventilation opening for under-floor spaces			
46	Show required covering of ventilation opening			
47	Show the required access opening to access to under-floor spaces			
	Show the sub-floor structural panel sheathing type, thickness and fastener schedule on the edges &			

48	intermediate of the areas structural panel sheathing			
49	Show Draftstopping, Fire caulking and Fire blocking			
50	Show fireproofing requirements for garages attached to living spaces, per FBCR section 309			
51	Provide live and dead load rating of floor framing systems (psf).			

FBCR CHAPTER 6 WOOD WALL FRAMING CONSTRUCTION

GENERAL REQUIREMENTS: APPLICANT – PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL		Items to Include- Each Box shall be Circled as Applicable		
		YES	NO	N/A
52	Stud type, grade, size, wall height and oc spacing for all load bearing or shear walls			
53	Fastener schedule for structural members per table FBCR 602.3 are to be shown			
54	Show Wood structural panel's sheathing attachment to studs, joist, trusses, rafters and structural members, showing fastener schedule attachment on the edges & intermediate of the areas structural panel sheathing			
55	Show all required connectors with a max uplift rating and required number of connectors and oc spacing for continuous connection of structural walls to foundation and roof trusses or rafter systems			
56	Show sizes, type, span lengths and required number of support jack studs, king studs for shear wall opening and girder or header per FBCR Table 502.5 (1)			
57	Indicate where pressure treated wood will be placed			
58	Show all wall structural panel sheathing, grade, thickness and show fastener schedule for structural panel sheathing edges & intermediate areas			
59	A detail showing gable truss bracing, wall balloon framing details or/ and wall hinge bracing detail			

FBCR :ROOF SYSTEMS:

60	Truss design drawing shall meet section FBCR 802.10 Wood trusses			
61	Include a layout and truss details, signed and sealed by Florida Professional Engineer			
62	Show types of connector's assemblies' and resistance uplift rating for all trusses and rafters			
63	Show gable ends with rake beams showing reinforcement or gable truss and wall bracing details			
64	Provide dead load rating of trusses			

FBCR 802:Conventional Roof Framing Layout

65	Rafter and ridge beams sizes, span, species and spacing			
66	Connectors to wall assemblies' include assemblies' resistance to uplift rating			
67	Valley framing and support details			
68	Provide dead load rating of rafter system			

FBCR Table 602,3(2) & FBCR 803 ROOF SHEATHING

69	Include all materials which will make up the roof decking, identification of structural panel sheathing, grade, thickness			
70	Show fastener Size and schedule for structural panel sheathing on the edges & intermediate areas			

FBCR ROOF ASSEMBLIES FRC Chapter 9

71	Include all materials which will make up the roof assembles covering			
72	Submit Florida Product Approval numbers for each component of the roof assembles covering			

FBCR Chapter 11 Energy Efficiency Code for residential building

Residential construction shall comply with this code by using the following compliance methods in the FBCR chapter 11 Residential buildings compliance methods. *Two of the required forms are to be submitted, showing dimensions condition area equal to the total condition living space area*

GENERAL REQUIREMENTS: APPLICANT – PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL		Items to Include- Each Box shall be Circled as Applicable		
		YES	NO	N/A
73	Show the insulation R value for the following areas of the structure			
74	Attic space			
75	Exterior wall cavity			
76	Crawl space			

HVAC information

77	Submit two copies of a Manual J sizing equipment or equivalent computation study			
78	Exhaust fans locations in bathrooms			
79	Show clothes dryer route and total run of exhaust duct			

Plumbing Fixture layout shown

80	All fixtures waste water lines shall be shown on the foundation plan			
81	Show the location of water heater			

Private Potable Water

82	Pump motor horse power			
83	Reservoir pressure tank gallon capacity			
84	Rating of cycle stop valve if used			

Electrical layout shown including

85	Switches, outlets/receptacles, lighting and all required GFCI outlets identified			
86	Ceiling fans			
87	Smoke detectors & Carbon dioxide detectors			
88	Service panel, sub-panel, location(s) and total ampere ratings			
89	On the electrical plans identify the electrical service overcurrent protection device for the main electrical service. This device shall be installed on the exterior of structures to serve as a disconnecting means for the utility company electrical service. Conductors used from the exterior disconnecting means to a panel or sub panel shall have four-wire conductors, of which one conductor shall be used as an equipment ground. Indicate if the utility company service entrance cable will be of the overhead or underground type.			

90	Appliances and HVAC equipment and disconnects			
91	Arc Fault Circuits (AFCI) in bedrooms			

Disclosure Statement for Owner Builders *If you as the applicant will be acting as an owner/builder under section 489.103(7) of the Florida Statutes, submit the required owner builder disclosure statement form.*

Notice Of Commencement

A notice of commencement form **recorded** in the Columbia County Clerk Office is required to be filed with the building department Before Any Inspections can be preformed.

GENERAL REQUIREMENTS: APPLICANT – PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL		Items to Include- Each Box shall be Circled as Applicable
---	--	--

THE FOLLOWING ITEMS MUST BE SUBMITTED WITH BUILDING PLANS

		YES	NO	N/A
92	Building Permit Application A current Building Permit Application form is to be completed and submitted for all residential projects			
93	Parcel Number The parcel number (Tax ID number) from the Property Appraiser (386) 758-1084 is required. A copy of property deed is also requested			
94	Environmental Health Permit or Sewer Tap Approval A copy of a approved Columbia County Environmental Health (386) 758-1058			
95	City of Lake City A permit showing an approved waste water sewer tap			
96	Toilet facilities shall be provided for all construction sites			
97	Town of Fort White (386) 497-2321 If the parcel in the application for building permit is within the Corporate city limits of Fort White an approval land use development letter issued by the Town of Fort is required to be submitted with the application for a building permit.			
98	Flood Information: All projects within the Floodway of the Suwannee or Santa Fe Rivers shall require permitting through the Suwannee River Water Management District, before submitting a application to this office. Any project located within a flood zone where the base flood elevation (100 year flood) has been established shall meet the requirements of Section 8.5.2 of the Columbia County Land Development Regulations. Any project located within a flood zone where the base flood elevation has not been established (Zone A) shall meet the requirements of Section 8.5.3 of the Columbia County Land Development Regulations			
99	CERTIFIED FINISHED FLOOR ELEVATIONS will be required on any project where the base flood elevation (100 year flood) has been established			
100	A development permit will also be required. Development permit cost is \$50.00			
101	Driveway Connection: If the property does not have an existing access to a public road, then an application for a culvert permit (\$25.00) must be made. If the applicant feels that a culvert is not needed, they may apply for a culvert waiver (\$50.00). All culvert waivers are sent to the Columbia County Public Works Department for approval or denial.			
102	911 Address: If the project is located in an area where a 911 address has not been issued, then application for a 911 address must be applied for and received through the Columbia County Emergency Management Office of 911 Addressing Department (386) 758-1125			

Section R101.2.1 of the Florida Building Code Residential:

The provisions of Chapter 1, Florida Building Code, Building shall govern the administration and enforcement of the Florida Building Code, Residential.

Section 105 of the Florida Building Code defines the:

Time limitation of application.

An application for a permit for any proposed work shall be deemed to have been abandoned 180 days after the date of filing, unless such application has been pursued in good faith or a permit has been issued; except that the building official is authorized to grant one or more extensions of time for additional periods not exceeding 90 days each. The extension shall be requested in writing and justifiable cause demonstrated.

Single-family residential dwelling.

Section 105.3.4 A building permit for a single-family residential dwelling must be issued within 30 working days of application therefor unless unusual circumstances require a longer time for processing the application or unless the permit application fails to satisfy the Florida Building Code or the enforcing agency's laws or ordinances.

Permit intent.

Section 105.4.1: A permit issued shall be constructed to be a license to proceed with the work and not as authority to violate, cancel, alter or set aside any of the provisions of the technical codes, nor shall issuance of a permit prevent the building official from thereafter requiring a correction of errors in plans, construction or violations of this code. Every permit issued shall become invalid unless the work authorized by such permit is commenced within six months after its issuance, or if the work authorized by such permit is suspended or abandoned for a period of six months after the time the work is commenced.

If work has commenced.

Section 105.4.1.1: If work has commenced and the permit is revoked, becomes null and void, or expires because of lack of progress or abandonment, a new permit covering the proposed construction shall be obtained before proceeding with the work.

New Permit.

Section 105.4.1.2: If a new permit is not obtained within 180 days from the date the initial permit became null and void, the building official is authorized to require that any work which has been commenced or completed be removed from the building site. Alternately, a new permit may be issued on application, providing the work in place and required to complete the structure meets all applicable regulations in effect at the time the initial permit became null and void and any regulations which may have become effective between the date of expiration and the date of issuance of the new permit.

Work Shall Be:

Section 105.4.1.3: Work shall be considered to be in active progress when the permit has received an approved inspection within 180 days. This provision shall not be applicable in case of civil commotion or strike or when the building work is halted due directly to judicial injunction, order or similar process.

The Fee:

Section 105.4.1.4: The fee for renewal reissuance and extension of a permit shall be set forth by the administrative authority.

When the submitted application is approved for permitting the applicant will be notified by phone as to the date and time a building permit will be prepared and issued by the Columbia County Building & Zoning Department



Project Information for: L278347

Builder: GIEBEIG HOMES
Lot : 13
Subdivision: MAYFAIR
County: COLUMBIA
Truss Count: 28
Design Program: MiTek 20/20 6.3
Building Code: FBC2004/TPI2002

Truss Design Load Information:

Gravity: **Wind:**

Roof (psf): 42.0 Wind Standard: ASCE 7-02 Wind Exposure: B
Floor (psf): N/A Wind Speed (mph): 110

Note: See the individual truss drawings for special loading conditions.

Contractor of Record, responsible for structural engineering:

Brian T. Giebeig Florida Registered Residential Contractor License No. RR282811523
Address: Trent Giebeig Construction, Inc. 462 Southwest Fairlington Court Lake City, Florida 32025

Truss Design Engineer: Julius Lee, PE Florida P.E. License No. 34869


Address: 1109 Coastal Bay Blvd. Boynton Beach, FL 33435

Notes:

1. Determination as to the suitability of these truss components for the structure is the responsibility of the building designer/engineer of record, as defined in ANSI/TPI 1-2002 Section 2.2
2. The seal date shown on the individual truss component drawings must match the seal date on this index sheet.
3. The Truss Design Engineer's responsibility relative to this structure consists solely of the design of the individual truss components and does not include the design of any additional structural elements including but not limited to continuous lateral bracing elements in the web and chord planes. See Florida Administrative Code 61G15-31.003 sections 3 c) & 5 and Chapter 2 of the National Design Standard for Metal Plate Connected Wood Truss Construction ANSI/TPI 1-2002 for additional information on the responsibilities of the delegated "Truss Design Engineer". Builders FirstSource and Julius Lee, PE do not accept any additional delegations beyond the scope of work described in the referenced documents above.




No.	Drwg. #	Truss ID	Date
1	J1966915	CJ1	5/23/08
2	J1966916	CJ3	5/23/08
3	J1966917	CJ5	5/23/08
4	J1966918	EJ3	5/23/08
5	J1966919	EJ7	5/23/08
6	J1966920	HJ4	5/23/08
7	J1966921	HJ9	5/23/08
8	J1966922	T01	5/23/08
9	J1966923	T02	5/23/08
10	J1966924	T03	5/23/08
11	J1966925	T04	5/23/08
12	J1966926	T05	5/23/08
13	J1966927	T06	5/23/08
14	J1966928	T07	5/23/08
15	J1966929	T08	5/23/08
16	J1966930	T09	5/23/08
17	J1966931	T10	5/23/08
18	J1966932	T11	5/23/08
19	J1966933	T12	5/23/08
20	J1966934	T13	5/23/08
21	J1966935	T14	5/23/08
22	J1966936	T15	5/23/08
23	J1966937	T16	5/23/08
24	J1966938	T17	5/23/08
25	J1966939	T18	5/23/08
26	J1966940	T19	5/23/08
27	J1966941	T20	5/23/08
28	J1966942	T21	5/23/08



Job	Truss	Truss Type	Qty	Ply	GIEBEIG HOMES - ST. JOHNS W/RP
L278347	CJ1	ROOF TRUSS	18	1	J1966915
Job Reference (optional)					

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Fri May 23 07:17:44 2008 Page 1



LOADING (psf)	SPACING	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plates Increase	1.25	TC 0.28	Vert(LL)	-0.00	2	>999	360	MT20	244/190
TCDL 7.0	Lumber Increase	1.25	BC 0.01	Vert(TL)	-0.00	2	>999	240		
BCLL 10.0	* Rep Stress Incr	YES	WB 0.00	Horz(TL)	0.00	3	n/a	n/a		
BCDL 5.0	Code FBC2004/TPI2002		(Matrix)							
										Weight: 7 lb

LUMBER

TOP CHORD 2 X 4 SYP No.2
BOT CHORD 2 X 4 SYP No.2

BRACING

TOP CHORD Structural wood sheathing directly applied or 1-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (lb/size) 2=256/0-3-8, 4=5/Mechanical, 3=-90/Mechanical
Max Horz 2=87(load case 6)
Max Uplift 2=-286(load case 6), 4=-9(load case 4), 3=-90(load case 1)
Max Grav 2=256(load case 1), 4=14(load case 2), 3=127(load case 6)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=0/47, 2-3=-69/75
BOT CHORD 2-4=0/0

JOINT STRESS INDEX

2 = 0.17

NOTES

- 1) Wind: ASCE 7-02; 110mph (3-second gust); h=13ft; TCDL=4.2psf; BCDL=3.0psf; Category II; Exp B; enclosed; MWFRS gable end zone and C-C Exterior(2) zone; porch left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60. This truss is designed for C-C for members and forces, and for MWFRS for reactions specified.
- 2) *This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) All bearings are assumed to be SYP No.2 crushing capacity of 565.00 psi
- 4) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 286 lb uplift at joint 2, 9 lb uplift at joint 4 and 90 lb uplift at joint 3.

Continued on page 2

Julius Lane
Truss Design Engineer
Florida License No. 34868
1100 Coastal Bay Blvd.
Boynton Beach, FL 33435

May 23, 2008

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE
This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	GIEBEIG HOMES - ST. JOHNS W/RP
L278347	CJ1	ROOF TRUSS	18	1	J1966915
Job Reference (optional)					

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Fri May 23 07:17:44 2008 Page 2

LOAD CASE(S) Standard

Julius Lee
Truss Design Engineer
Florida P.E. No. 31868
1100 Coastal Bay Blvd
Boynton Beach, FL 33435

May 23, 2008


Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE
This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling, Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	GIEBEIG HOMES - ST. JOHNS W/RP
L278347	CJ3	ROOF TRUSS	14	1	J1966916
Job Reference (optional)					

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Fri May 23 07:17:44 2008 Page 1



LOADING (psf)	SPACING	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plates Increase	1.25	TC 0.29	Vert(LL)	0.01	2-4	>999	360	MT20	244/190
TCDL 7.0	Lumber Increase	1.25	BC 0.08	Vert(TL)	-0.01	2-4	>999	240		
BCLL 10.0	* Rep Stress Incr	YES	WB 0.00	Horz(TL)	-0.00	3	n/a	n/a		
BCDL 5.0	Code FBC2004/TPI2002		(Matrix)						Weight: 13 lb	

LUMBER

TOP CHORD 2 X 4 SYP No.2
BOT CHORD 2 X 4 SYP No.2

BRACING

TOP CHORD Structural wood sheathing directly applied or
3-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc
bracing.

REACTIONS (lb/size) 3=31/Mechanical, 2=250/0-3-8, 4=14/Mechanical
Max Horz 2=132(load case 6)
Max Uplift 3=-28(load case 7), 2=-238(load case 6), 4=-27(load case 4)
Max Grav 3=31(load case 1), 2=250(load case 1), 4=42(load case 2)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=0/47, 2-3=-57/7
BOT CHORD 2-4=0/0

JOINT STRESS INDEX

2 = 0.15

NOTES

- 1) Wind: ASCE 7-02; 110mph (3-second gust); h=13ft; TCDL=4.2psf; BCDL=3.0psf; Category II; Exp B; enclosed; MWFRS gable end zone and C-C Exterior(2) zone; porch left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60. This truss is designed for C-C for members and forces, and for MWFRS for reactions specified.
- 2) *This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) All bearings are assumed to be SYP No.2 crushing capacity of 565.00 psi
- 4) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 28 lb uplift at joint 3, 238 lb uplift at joint 2 and 27 lb uplift at joint 4.

Julius Lee
Truss Design Engineer
Florida PE No. 21888
1100 Coastal Bay Blvd.
Boynton Beach, FL 33435

May 23, 2008

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE
This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	GIEBEIG HOMES - ST. JOHNS W/RP
L278347	CJ3	ROOF TRUSS	14	1	J1966916
Job Reference (optional)					

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Fri May 23 07:17:44 2008 Page 2

LOAD CASE(S) Standard

Julius Lee
Truss Design Engineer
Florida PE No. 34868
1409 Coastal Bay Blvd
Boynton Beach, FL 33435

May 23, 2008


Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE
This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	GIEBEIG HOMES - ST. JOHNS W/RP
L278347	CJ5	ROOF TRUSS	14	1	J1966917
Job Reference (optional)					

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Fri May 23 07:17:45 2008 Page 1



LOADING (psf)	SPACING	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plates Increase	1.25	TC 0.29	Vert(LL)	0.09	2-4	>663	360	MT20	244/190
TCDL 7.0	Lumber Increase	1.25	BC 0.24	Vert(TL)	-0.05	2-4	>999	240		
BCLL 10.0	* Rep Stress Incr	YES	WB 0.00	Horz(TL)	-0.00	3	n/a	n/a		
BCDL 5.0	Code FBC2004/TPI2002		(Matrix)							
Weight: 19 lb										

LUMBER

TOP CHORD 2 X 4 SYP No.2
BOT CHORD 2 X 4 SYP No.2

BRACING

TOP CHORD Structural wood sheathing directly applied or 5-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (lb/size) 3=103/Mechanical, 2=295/0-3-8, 4=24/Mechanical
Max Horz 2=178(load case 6)
Max Uplift 3=-87(load case 6), 2=-260(load case 6), 4=-46(load case 4)
Max Grav 3=103(load case 1), 2=295(load case 1), 4=72(load case 2)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=0/47, 2-3=-88/36
BOT CHORD 2-4=0/0

JOINT STRESS INDEX

2 = 0.17

NOTES

- 1) Wind: ASCE 7-02; 110mph (3-second gust); h=13ft; TCDL=4.2psf; BCDL=3.0psf; Category II; Exp B; enclosed; MWFRS gable end zone and C-C Exterior(2) zone; porch left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60. This truss is designed for C-C for members and forces, and for MWFRS for reactions specified.
- 2) *This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) All bearings are assumed to be SYP No.2 crushing capacity of 565.00 psi
- 4) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 87 lb uplift at joint 3, 260 lb uplift at joint 2 and 46 lb uplift at joint 4.

Julius Lee
Truss Design Engineer
Florida PE No. 34888
1100 Coastal Bay Blvd
Boynton Beach, FL 33426

May 23, 2008

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE
This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Oonofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	GIEBEIG HOMES - ST. JOHNS W/RP
L278347	CJ5	ROOF TRUSS	14	1	J1966917
Job Reference (optional)					

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Fri May 23 07:17:45 2008 Page 2

LOAD CASE(S) Standard

Julius Lee
Truss Design Engineer
Florida P.E. No. 31868
1100 Coastal Bay Blvd
Boynton Beach, FL 33435

May 23, 2008

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE


This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	GIEBEIG HOMES - ST. JOHNS W/RP
L278347	EJ3	ROOF TRUSS	3	1	J1966918
Job Reference (optional)					

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Fri May 23 07:17:46 2008 Page 1



LOADING (psf)	SPACING	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plates Increase	1.25	TC 0.29	Vert(LL)	0.01	2-4	>999	360	MT20	244/190
TCDL 7.0	Lumber Increase	1.25	BC 0.08	Vert(TL)	-0.01	2-4	>999	240		
BCLL 10.0	* Rep Stress Incr	YES	WB 0.00	Horz(TL)	-0.00	3	n/a	n/a		
BCDL 5.0	Code FBC2004/TPI2002		(Matrix)							
									Weight: 13 lb	

LUMBER

TOP CHORD 2 X 4 SYP No.2
BOT CHORD 2 X 4 SYP No.2

BRACING

TOP CHORD Structural wood sheathing directly applied or
3-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc
bracing.

REACTIONS (lb/size) 3=31/Mechanical, 2=250/0-3-8, 4=14/Mechanical
Max Horz 2=132(load case 6)
Max Uplift 3=-28(load case 7), 2=-238(load case 6), 4=-27(load case 4)
Max Grav 3=31(load case 1), 2=250(load case 1), 4=42(load case 2)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=0/47, 2-3=-57/7
BOT CHORD 2-4=0/0

JOINT STRESS INDEX

2 = 0.15

NOTES

- 1) Wind: ASCE 7-02; 110mph (3-second gust); h=13ft; TCDL=4.2psf; BCDL=3.0psf; Category II; Exp B; enclosed; MWFRS gable end zone and C-C Exterior(2) zone; porch left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60. This truss is designed for C-C for members and forces, and for MWFRS for reactions specified.
- 2) *This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) All bearings are assumed to be SYP No.2 crushing capacity of 565.00 psi
- 4) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 28 lb uplift at joint 3, 238 lb uplift at joint 2 and 27 lb uplift at joint 4.

Julius Lee
Truss Design Engineer
Florida PE No. 35888
1100 Coastal Bay Blvd
Boynton Beach, FL 33435

May 23, 2008

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE
This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	GIEBEIG HOMES - ST. JOHNS W/RP
L278347	EJ3	ROOF TRUSS	3	1	J1966918
Job Reference (optional)					

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Fri May 23 07:17:46 2008 Page 2

LOAD CASE(S) Standard

Julius Lane
Truss Design Engineer
Florida PE No. 37868
1409 Coastal Bay Blvd
Boynton Beach, FL 33435

May 23, 2008

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE

This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job L278347	Truss EJ7	Truss Type ROOF TRUSS	Qty 27	Ply 1	GEIBEIG HOMES - ST.JOHNS 4 W/P J1966919
Builders FirstSource, Lake City, FL 32055					Job Reference (optional)

6.300 s Apr 19 2006 MiTek Industries, Inc. Fri May 23 08:53:32 2008 Page 1




Plate Offsets (X,Y): [2:0-2-4,0-1-8]

LOADING (psf)	SPACING	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plates Increase	1.25	TC 0.50	Vert(LL)	0.33	2-4	>250	360	MT20	244/190
TCDL 7.0	Lumber Increase	1.25	BC 0.45	Vert(TL)	-0.16	2-4	>501	240		
BCLL 10.0	Rep Stress Incr	YES	WB 0.00	Horz(TL)	-0.00	3	n/a	n/a		
BCDL 5.0	Code FBC2004/TPI2002		(Matrix)							
									Weight: 26 lb	

LUMBER

TOP CHORD 2 X 4 SYP No.2
BOT CHORD 2 X 4 SYP No.2

BRACING

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (lb/size) 3=154/Mechanical, 2=352/0-3-8, 4=45/Mechanical

Max Horz 2=161(load case 6)
Max Uplift 3=-94(load case 6), 2=-224(load case 6), 4=-65(load case 5)
Max Grav 3=154(load case 1), 2=352(load case 1), 4=94(load case 2)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=0/47, 2-3=-131/54
BOT CHORD 2-4=0/0

JOINT STRESS INDEX

2 = 0.68

Julius Lee
Truss Design Engineer
Florida PE No. 34888
1100 Coastal Bay Blvd
Boynton Beach, FL 33435

May 23, 2008

Continued on page 2

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE
This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job L278347	Truss EJ7	Truss Type ROOF TRUSS	Qty 27	Ply 1	GEIBEIG HOMES - ST.JOHNS 4 W/P J1966919 Job Reference (optional)
----------------	--------------	--------------------------	-----------	----------	--

Builders FirstSource, Lake City, FL 32055

6.300 s Apr 19 2006 MiTek Industries, Inc. Fri May 23 08:53:32 2008 Page 2

NOTES

- 1) Wind: ASCE 7-02; 110mph (3-second gust); h=13ft; TCDL=4.2psf; BCDL=3.0psf; Category II; Exp B; enclosed; MWFRS and C-C Exterior(2) zone; porch left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60. This truss is designed for C-C for members and forces, and for MWFRS for reactions specified.
- 2) *This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) All bearings are assumed to be SYP No.2 crushing capacity of 565.00 psi
- 4) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 94 lb uplift at joint 3, 224 lb uplift at joint 2 and 65 lb uplift at joint 4.

LOAD CASE(S) Standard

Julius Lee
Truss Design Engineer
Florida PE No. 34869
1100 Coastal Bay Blvd.
Boynton Beach, FL 33435

May 23, 2008

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE


This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	GIEBEIG HOMES - ST. JOHNS W/RP
L278347	HJ4	ROOF TRUSS	2	1	J1966920
Job Reference (optional)					

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Fri May 23 07:17:47 2008 Page 1



LOADING (psf)	SPACING	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plates Increase	1.25	TC 0.53	Vert(LL)	0.02	2-4	>999	360	MT20	244/190
TCDL 7.0	Lumber Increase	1.25	BC 0.10	Vert(TL)	-0.02	2-4	>999	240		
BCLL 10.0	* Rep Stress Incr	NO	WB 0.00	Horz(TL)	-0.00	3	n/a	n/a		
BCDL 5.0	Code FBC2004/TPI2002		(Matrix)							
									Weight: 18 lb	

LUMBER

TOP CHORD 2 X 4 SYP No.2
BOT CHORD 2 X 4 SYP No.2

BRACING

TOP CHORD Structural wood sheathing directly applied or
4-2-15 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc
bracing.

REACTIONS (lb/size) 3=15/Mechanical, 2=275/0-4-15, 4=14/Mechanical
Max Horz 2=98(load case 3)
Max Uplift 3=-6(load case 6), 2=-302(load case 3), 4=-41(load case 3)
Max Grav 3=32(load case 7), 2=275(load case 1), 4=54(load case 2)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=0/50, 2-3=-37/10
BOT CHORD 2-4=0/0

JOINT STRESS INDEX

2 = 0.13

NOTES

- 1) Wind: ASCE 7-02; 110mph (3-second gust); h=13ft; TCDL=4.2psf; BCDL=3.0psf; Category II; Exp B; enclosed; MWFRS gable end zone; porch left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60.
- 2) *This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) All bearings are assumed to be SYP No.2 crushing capacity of 565.00 psi
- 4) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 6 lb uplift at joint 3, 302 lb uplift at joint 2 and 41 lb uplift at joint 4.

Julius L. Lauer
Truss Design Engineer
Florida Reg. No. 31888
1100 Coastal Bay Blvd
Boynton Beach, FL 33426

Continued on page 2

May 23, 2008

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE
This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	GIEBEIG HOMES - ST. JOHNS W/RP
L278347	HJ4	ROOF TRUSS	2	1	J1966920
Job Reference (optional)					

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Fri May 23 07:17:47 2008 Page 2

NOTES

5) In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

LOAD CASE(S) Standard

1) Regular: Lumber Increase=1.25, Plate Increase=1.25

Uniform Loads (plf)

Vert: 1-2=-54

Trapezoidal Loads (plf)

Vert: 2=-3(F=26, B=26)-to-3=-57(F=-2, B=-2), 2=-0(F=5, B=5)-to-4=-11(F=-0, B=-0)

Julius Lee
Truss Design Engineer
Florida P.E. No. 34868
1100 Coastal Bay Blvd
Boynton Beach, FL 33426

May 23, 2008

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE


This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	GIEBEIG HOMES - ST. JOHNS W/RP
L278347	HJ9	ROOF TRUSS	7	1	J1966921
Job Reference (optional)					

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Fri May 23 07:17:47 2008 Page 1



LOADING (psf)	SPACING	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plates Increase	1.25	TC 0.60	Vert(LL)	0.09	6-7	>999	360	MT20	244/190
TCDL 7.0	Lumber Increase	1.25	BC 0.40	Vert(TL)	-0.11	6-7	>999	240		
BCLL 10.0	* Rep Stress Incr	NO	WB 0.36	Horz(TL)	0.01	5	n/a	n/a		
BCDL 5.0	Code FBC2004/TPI2002		(Matrix)						Weight: 45 lb	

LUMBER

TOP CHORD 2 X 4 SYP No.2
BOT CHORD 2 X 4 SYP No.2
WEBS 2 X 4 SYP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 7-11-7 oc bracing.

REACTIONS (lb/size) 4=267/Mechanical, 2=453/0-4-15, 5=220/Mechanical
Max Horz 2=269(load case 3)
Max Uplift 4=-233(load case 3), 2=-399(load case 3), 5=-183(load case 3)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=0/50, 2-3=-650/365, 3-4=-105/65
BOT CHORD 2-7=-538/603, 6-7=-538/603, 5-6=0/0
WEBS 3-7=-89/186, 3-6=-627/559

JOINT STRESS INDEX

2 = 0.76, 3 = 0.25, 6 = 0.21 and 7 = 0.13

NOTES

- 1) Wind: ASCE 7-02; 110mph (3-second gust); h=13ft; TCDL=4.2psf; BCDL=3.0psf; Category II; Exp B; enclosed; MWFRS gable end zone; porch left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60.
- 2) *This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) All bearings are assumed to be SYP No.2 crushing capacity of 565.00 psi
- 4) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 233 lb uplift at joint 4, 399 lb uplift at joint 2 and 183 lb uplift at joint 5.

Julius Lane
Truss Design Engineer
Florida P.E. No. 25868
1309 Coastal Bay Blvd
Boynton Beach, FL 33435

Continued on page 2

May 23, 2008

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE
This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	GIEBEIG HOMES - ST. JOHNS W/RP
L278347	HJ9	ROOF TRUSS	7	1	J1966921
					Job Reference (optional)

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Fri May 23 07:17:47 2008 Page 2

NOTES

5) In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

LOAD CASE(S) Standard

1) Regular: Lumber Increase=1.25, Plate Increase=1.25

Uniform Loads (plf)

Vert: 1-2=-54

Trapezoidal Loads (plf)

Vert: 2=-3(F=26, B=26)-to-4=-134(F=-40, B=-40), 2=-0(F=5, B=5)-to-5=-25(F=-7, B=-7)

Julius Lane
Truss Design Engineer
Florida P.E. No. 24888
1300 Coastal Bay Blvd
Boynton Beach, FL 33435

May 23, 2008

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE

This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	GIEBEIG HOMES - ST. JOHNS W/RP
L278347	T01	ROOF TRUSS	1	1	J1966922
Job Reference (optional)					

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Fri May 23 07:17:48 2008 Page 1




Plate Offsets (X,Y): [2:0-8-0,0-0-6], [5:0-8-0,0-0-6]

LOADING (psf)	SPACING	2-0-0	CSI	DEFL	in	(loc)	I/defl	L/d	PLATES	GRIP
TCLL 20.0	Plates Increase	1.25	TC 0.53	Vert(LL)	-0.09	7-9	>999	360	MT20	244/190
TCDL 7.0	Lumber Increase	1.25	BC 0.48	Vert(TL)	-0.19	7-9	>999	240		
BCLL 10.0	* Rep Stress Incr	NO	WB 0.18	Horz(TL)	0.07	5	n/a	n/a		
BCDL 5.0	Code FBC2004/TPI2002		(Matrix)						Weight: 88 lb	

LUMBER

TOP CHORD 2 X 4 SYP No.2
BOT CHORD 2 X 4 SYP No.2
WEBS 2 X 4 SYP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied or 3-8-5 oc purlins.
BOT CHORD Rigid ceiling directly applied or 8-0-10 oc bracing.

REACTIONS (lb/size) 2=1381/0-3-8, 5=1381/0-3-8
Max Horz 2=77(load case 5)
Max Uplift 2=-474(load case 5), 5=-474(load case 6)

FORCES (lb) - Maximum Compression/Maximum Tension
TOP CHORD 1-2=0/47, 2-3=-2416/730, 3-4=-2101/687, 4-5=-2415/730, 5-6=0/47
BOT CHORD 2-9=-619/2080, 8-9=-590/2100, 7-8=-590/2100, 5-7=-586/2079
WEBS 3-9=-125/568, 4-9=-124/126, 4-7=-108/516

JOINT STRESS INDEX

2 = 0.74, 3 = 0.80, 4 = 0.98, 5 = 0.74, 7 = 0.37, 8 = 0.77 and 9 = 0.41

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-02; 110mph (3-second gust); h=13ft; TCDL=4.2psf; BCDL=3.0psf; Category II; Exp B; enclosed; MWFRS; Lumber DOL=1.60 plate grip DOL=1.60.
- Provide adequate drainage to prevent water ponding.
- *This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- All bearings are assumed to be SYP No.2 crushing capacity of 565.00 psi

Julius Lee
Truss Design Engineer
Florida PE No. 34868
1100 Coastal Bay Blvd
Boynton Beach, FL 33435

Continued on page 2

May 23, 2008

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE
This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	GIEBEIG HOMES - ST. JOHNS W/RP
L278347	T01	ROOF TRUSS	1	1	J1966922
Job Reference (optional)					

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Fri May 23 07:17:48 2008 Page 2

NOTES

- 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 474 lb uplift at joint 2 and 474 lb uplift at joint 5.
- 7) In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

LOAD CASE(S) Standard

- 1) Regular: Lumber Increase=1.25, Plate Increase=1.25

Uniform Loads (plf)

Vert: 1-3=-54, 3-4=-118(F=-64), 4-6=-54, 2-9=-10, 7-9=-22(F=-12), 5-7=-10

Concentrated Loads (lb)

Vert: 9=-411(F) 7=-411(F)

Julius Lee
Truss Design Engineer
Florida PE No. 34868
1400 Coastal Bay Blvd.
Boynton Beach, FL 33435

May 23, 2008

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE

This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	GIEBEIG HOMES - ST. JOHNS W/RP
L278347	T02	ROOF TRUSS	1	1	J1966923
Job Reference (optional)					

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Fri May 23 07:17:49 2008 Page 1




Plate Offsets (X,Y): [2:0-1-5,0-0-7], [7:0-1-5,0-0-7]

LOADING (psf)	SPACING		CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plates Increase	2-0-0	TC 0.29	Vert(LL)	-0.13	2-11	>999	360	MT20	244/190
TCDL 7.0	Lumber Increase	1.25	BC 0.42	Vert(TL)	-0.25	2-11	>965	240		
BCLL 10.0	* Rep Stress Incr	YES	WB 0.12	Horz(TL)	0.03	7	n/a	n/a		
BCDL 5.0	Code FBC2004/TPI2002		(Matrix)						Weight: 104 lb	

LUMBER

TOP CHORD 2 X 4 SYP No.2
BOT CHORD 2 X 4 SYP No.2
WEBS 2 X 4 SYP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (lb/size) 2=747/0-3-8, 7=747/0-3-8
Max Horz 2=-89(load case 7)
Max Uplift 2=-229(load case 6), 7=-229(load case 7)

FORCES (lb) - Maximum Compression/Maximum Tension
TOP CHORD 1-2=0/47, 2-3=-1067/567, 3-4=-805/447, 4-5=-675/453, 5-6=-806/448, 6-7=-1067/567, 7-8=0/47
BOT CHORD 2-11=-346/898, 10-11=-143/674, 9-10=-143/674, 7-9=-346/898
WEBS 3-11=-258/229, 4-11=-61/210, 5-9=-61/209, 6-9=-257/228, 4-9=-104/109

JOINT STRESS INDEX

2 = 0.85, 3 = 0.33, 4 = 0.34, 5 = 0.50, 6 = 0.33, 7 = 0.85, 9 = 0.64, 10 = 0.78 and 11 = 0.39

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-02; 110mph (3-second gust); h=13ft; TCDL=4.2psf; BCDL=3.0psf; Category II; Exp B; enclosed; MWFRS and C-C Exterior(2) zone; Lumber DOL=1.60 plate grip DOL=1.60. This truss is designed for C-C for members and forces, and for MWFRS for reactions specified.
- Provide adequate drainage to prevent water ponding.
- *This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.

Julius Lee
Truss Design Engineer
Florida PE No. 34868
1100 Coastal Bay Blvd
Boynton Beach, FL 33435

May 23, 2008

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE
This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	GIEBEIG HOMES - ST. JOHNS W/RP
L278347	T02	ROOF TRUSS	1	1	J1966923
Job Reference (optional)					

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Fri May 23 07:17:49 2008 Page 2

NOTES

- 5) All bearings are assumed to be SYP No.2 crushing capacity of 565.00 psi
- 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 229 lb uplift at joint 2 and 229 lb uplift at joint 7.

LOAD CASE(S) Standard

Julius Lee
Truss Design Engineer
Florida P.E. No. 31868
1100 Coastal Bay Blvd
Boynton Beach, FL 33435


May 23, 2008

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE

This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	GIEBEIG HOMES - ST. JOHNS W/RP
L278347	T03	ROOF TRUSS	5	1	J1966924
					Job Reference (optional)



LOADING (psf)	SPACING	2-0-0	CSI	DEFL	in	(loc)	I/defl	L/d	PLATES	GRIP
TCLL 20.0	Plates Increase	1.25	TC 0.36	Vert(LL)	0.24	8-10	>989	360	MT20	244/190
TCDL 7.0	Lumber Increase	1.25	BC 0.66	Vert(TL)	-0.37	8-10	>640	240		
BCLL 10.0	* Rep Stress Incr	NO	WB 0.18	Horz(TL)	0.04	6	n/a	n/a		
BCDL 5.0	Code FBC2004/TPI2002		(Matrix)							
									Weight: 97 lb	

LUMBER

TOP CHORD 2 X 4 SYP No.2
BOT CHORD 2 X 4 SYP No.2
WEBS 2 X 4 SYP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied or 4-9-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 7-9-10 oc bracing.

REACTIONS (lb/size) 2=960/0-3-8, 6=960/0-3-8
Max Horz 2=-95(load case 7)
Max Uplift 2=-292(load case 6), 6=-292(load case 7)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=0/47, 2-3=-1609/870, 3-4=-1438/813, 4-5=-1438/813, 5-6=-1609/870, 6-7=0/47
BOT CHORD 2-10=-621/1374, 9-10=-316/925, 8-9=-316/925, 6-8=-621/1374
WEBS 3-10=-216/200, 4-10=-263/547, 4-8=-263/547, 5-8=-216/200

JOINT STRESS INDEX

2 = 0.69, 3 = 0.33, 4 = 0.82, 5 = 0.33, 6 = 0.69, 8 = 0.40, 9 = 0.64 and 10 = 0.40

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-02; 110mph (3-second gust); h=13ft; TCDL=4.2psf; BCDL=3.0psf; Category II; Exp B; enclosed; MWFRS and C-C Exterior(2) zone; Lumber DOL=1.60 plate grip DOL=1.60. This truss is designed for C-C for members and forces, and for MWFRS for reactions specified.
- *This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- All bearings are assumed to be SYP No.2 crushing capacity of 565.00 psi
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 292 lb uplift at joint 2 and 292 lb uplift at joint 6.

Julian Lane
Truss Design Engineer
Florida P.E. No. 24888
1109 Coastal Bay Blvd.
Boynton Beach, FL 33435

May 23, 2008

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITTEK REFERENCE PAGE MII-7473 BEFORE USE
This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	GIEBEIG HOMES - ST. JOHNS W/RP
L278347	T03	ROOF TRUSS	5	1	J1966924
Job Reference (optional)					

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Fri May 23 07:17:50 2008 Page 2

NOTES

6) In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

LOAD CASE(S) Standard

1) Regular: Lumber Increase=1.25, Plate Increase=1.25

Uniform Loads (plf)

Vert: 1-4=-54, 4-7=-54, 2-10=-10, 8-10=-70(F=-60), 6-8=-10

Julius Lars
Truss Design Engineer
Florida License No. 34888
1409 Coastal Bay Blvd
Boynton Beach, FL 33435

May 23, 2008

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE

This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	GIEBEIG HOMES - ST. JOHNS W/RP
L278347	T04	ROOF TRUSS	1	1	J1966925
Job Reference (optional)					

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Fri May 23 07:17:51 2008 Page 1




Plate Offsets (X,Y): [2:0-1-13,Edge], [7:0-1-13,Edge], [9:0-3-8,0-1-8], [10:0-3-8,0-3-4], [11:0-3-8,0-1-8]

LOADING (psf)	SPACING		CSI	DEFL	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plates Increase	2-0-0	TC 0.61	Vert(LL)	-0.31	10	>999	360	MT20
TCDL 7.0	Lumber Increase	1.25	BC 0.99	Vert(TL)	-0.63	10-11	>565	240	244/190
BCLL 10.0	* Rep Stress Incr	NO	WB 0.97	Horz(TL)	0.20	7	n/a	n/a	
BCDL 5.0	Code FBC2004/TPI2002		(Matrix)						Weight: 139 lb

LUMBER

TOP CHORD 2 X 4 SYP No.2
BOT CHORD 2 X 4 SYP No.2
WEBS 2 X 4 SYP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied or 2-6-7 oc purlins.
BOT CHORD Rigid ceiling directly applied or 5-2-2 oc bracing.

REACTIONS (lb/size) 2=2084/0-3-8, 7=2084/0-3-8
Max Horz 2=-77(load case 6)
Max Uplift 2=-660(load case 5), 7=-660(load case 6)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=0/47, 2-3=-3937/1255, 3-4=-3479/1162, 4-5=-4602/1496, 5-6=-3479/1162, 6-7=-3937/1255, 7-8=0/47
BOT CHORD 2-11=-1083/3426, 10-11=-1482/4531, 9-10=-1464/4531, 7-9=-1049/3426
WEBS 3-11=-388/1308, 4-11=-1374/541, 4-10=0/216, 5-10=0/216, 5-9=-1374/541, 6-9=-388/1308

JOINT STRESS INDEX

2 = 0.83, 3 = 0.76, 4 = 0.45, 5 = 0.45, 6 = 0.76, 7 = 0.83, 9 = 0.82, 10 = 0.91 and 11 = 0.82

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-02; 110mph (3-second gust); h=13ft; TCDL=4.2psf; BCDL=3.0psf; Category II; Exp B; enclosed; MWFRS; Lumber DOL=1.60 plate grip DOL=1.60.
- Provide adequate drainage to prevent water ponding.
- *This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.

Continued on page 2

Julius Lee
Truss Design Engineer
Florida PE No. 34868
1109 Coastal Bay Blvd
Boynton Beach, FL 33435

May 23, 2008

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE
This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	GIEBEIG HOMES - ST. JOHNS W/RP
L278347	T04	ROOF TRUSS	1	1	J1966925
Job Reference (optional)					

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Fri May 23 07:17:51 2008 Page 2

NOTES

- 5) All bearings are assumed to be SYP No.2 crushing capacity of 565.00 psi
- 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 660 lb uplift at joint 2 and 660 lb uplift at joint 7.
- 7) In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

LOAD CASE(S) Standard

- 1) Regular: Lumber Increase=1.25, Plate Increase=1.25

Uniform Loads (plf)

Vert: 1-3=-54, 3-6=-118(F=-64), 6-8=-54, 2-11=-10, 9-11=-22(F=-12), 7-9=-10

Concentrated Loads (lb)

Vert: 11=-411(F) 9=-411(F)

Julius Lee
Truss Design Engineer
Florida PE No. 34868
1400 Coastal Bay Blvd.
Boynton Beach, FL 33435

May 23, 2008

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE

This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	GIEBEIG HOMES - ST. JOHNS W/RP
L278347	T05	ROOF TRUSS	1	1	J1966926
Job Reference (optional)					

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Fri May 23 07:17:52 2008 Page 1




Plate Offsets (X,Y): [2:0-1-5,0-0-7], [8:0-1-5,0-0-7], [11:0-3-0,0-3-0]

LOADING (psf)	SPACING	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plates Increase	1.25	TC 0.31	Vert(LL)	-0.15	2-12	>999	360	MT20	244/190
TCDL 7.0	Lumber Increase	1.25	BC 0.52	Vert(TL)	-0.29	2-12	>999	240		
BCLL 10.0	* Rep Stress Incr	YES	WB 0.38	Horz(TL)	0.08	8	n/a	n/a		
BCDL 5.0	Code FBC2004/TPI2002		(Matrix)						Weight: 154 lb	

LUMBER

TOP CHORD 2 X 4 SYP No.2
BOT CHORD 2 X 4 SYP No.2
WEBS 2 X 4 SYP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied or 4-8-4 oc purlins.
BOT CHORD Rigid ceiling directly applied or 7-8-15 oc bracing.

REACTIONS (lb/size) 2=1069/0-3-8, 8=1069/0-3-8
Max Horz 2=89(load case 6)
Max Uplift 2=-267(load case 6), 8=-267(load case 7)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=0/47, 2-3=-1745/913, 3-4=-1515/815, 4-5=-1325/788, 5-6=-1325/788, 6-7=-1515/815, 7-8=-1745/913, 8-9=0/47
BOT CHORD 2-12=-649/1494, 11-12=-617/1570, 10-11=-617/1570, 8-10=-650/1494
WEBS 3-12=-208/198, 4-12=-138/397, 5-12=-401/176, 5-11=0/128, 5-10=-401/176, 6-10=-138/397, 7-10=-208/198

JOINT STRESS INDEX

2 = 0.82, 3 = 0.33, 4 = 0.60, 5 = 0.56, 6 = 0.60, 7 = 0.33, 8 = 0.82, 10 = 0.56, 11 = 0.37 and 12 = 0.56

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-02; 110mph (3-second gust); h=13ft; TCDL=4.2psf; BCDL=3.0psf; Category II; Exp B; enclosed; MWFRS and C-C Exterior(2) zone; Lumber DOL=1.60 plate grip DOL=1.60. This truss is designed for C-C for members and forces, and for MWFRS for reactions specified.
- Provide adequate drainage to prevent water ponding.

Julius Lee
Truss Design Engineer
Florida PE No. 21868
1100 Coastal Bay Blvd.
Boynton Beach, FL 33435

Continued on page 2

May 23, 2008

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE
This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	GIEBEIG HOMES - ST. JOHNS W/RP
L278347	T05	ROOF TRUSS	1	1	J1966926
Job Reference (optional)					

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Fri May 23 07:17:52 2008 Page 2

NOTES

- 4) *This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 5) All bearings are assumed to be SYP No.2 crushing capacity of 565.00 psi
- 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 267 lb uplift at joint 2 and 267 lb uplift at joint 8.

LOAD CASE(S) Standard

Julius Lee
Truss Design Engineer
Florida P.E. No. 34828
1400 Coastal Bay Blvd
Boynton Beach, FL 33435

May 23, 2008

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE
This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	GIEBEIG HOMES - ST. JOHNS W/RP
L278347	T06	ROOF TRUSS	1	1	J1966927
Job Reference (optional)					

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Fri May 23 07:17:53 2008 Page 1




Plate Offsets (X,Y): [2:0-1-9,0-0-7], [8:0-1-9,0-0-7], [11:0-4-0,0-3-0]

LOADING (psf)	SPACING	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plates Increase	1.25	TC 0.31	Vert(LL)	-0.10	2-12	>999	360	MT20	244/190
TCDL 7.0	Lumber Increase	1.25	BC 0.38	Vert(TL)	-0.20	2-12	>999	240		
BCLL 10.0	* Rep Stress Incr	YES	WB 0.11	Horz(TL)	0.07	8	n/a	n/a		
BCDL 5.0	Code FBC2004/TPI2002		(Matrix)						Weight: 157 lb	

LUMBER

TOP CHORD 2 X 4 SYP No.2
BOT CHORD 2 X 4 SYP No.2
WEBS 2 X 4 SYP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied or 4-8-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 7-7-4 oc bracing.

REACTIONS (lb/size) 2=1069/0-3-8, 8=1069/0-3-8
Max Horz 2=-101(load case 7)
Max Uplift 2=-280(load case 6), 8=-280(load case 7)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=0/47, 2-3=-1762/938, 3-4=-1531/851, 4-5=-1268/798, 5-6=-1268/798, 6-7=-1531/851, 7-8=-1762/938, 8-9=0/47
BOT CHORD 2-12=-675/1511, 11-12=-417/1186, 10-11=-417/1186, 8-10=-675/1511
WEBS 3-12=-269/264, 4-12=-116/322, 4-11=-78/263, 5-11=-190/87, 6-11=-78/263, 6-10=-116/322, 7-10=-269/264

JOINT STRESS INDEX

2 = 0.75, 3 = 0.33, 4 = 0.50, 5 = 0.33, 6 = 0.50, 7 = 0.33, 8 = 0.75, 10 = 0.44, 11 = 0.34 and 12 = 0.44

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-02; 110mph (3-second gust); h=13ft; TCDL=4.2psf; BCDL=3.0psf; Category II; Exp B; enclosed; MWFRS and C-C Exterior(2) zone; Lumber DOL=1.60 plate grip DOL=1.60. This truss is designed for C-C for members and forces, and for MWFRS for reactions specified.
- Provide adequate drainage to prevent water ponding.

Julius Lee
Truss Design Engineer
Florida PE No. 34868
1100 Coastal Bay Blvd.
Boynton Beach, FL 33435

Continued on page 2

May 23, 2008

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE
This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	GIEBEIG HOMES - ST. JOHNS W/RP
L278347	T06	ROOF TRUSS	1	1	J1966927
Job Reference (optional)					

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Fri May 23 07:17:53 2008 Page 2

NOTES

- 4) *This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 5) All bearings are assumed to be SYP No.2 crushing capacity of 565.00 psi
- 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 280 lb uplift at joint 2 and 280 lb uplift at joint 8.

LOAD CASE(S) Standard

Julius Lee
Truss Design Engineer
Florida PE No. 34868
1100 Coastal Bay Blvd.
Boynton Beach, FL 33435

May 23, 2008

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE

This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	GIEBEIG HOMES - ST. JOHNS W/RP
L278347	T07	ROOF TRUSS	1	1	J1966928
Job Reference (optional)					

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Fri May 23 07:17:54 2008 Page 2

NOTES

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-02; 110mph (3-second gust); h=13ft; TCDL=4.2psf; BCDL=3.0psf; Category II; Exp B; enclosed; MWFRS and C-C Exterior(2) zone; Lumber DOL=1.60 plate grip DOL=1.60. This truss is designed for C-C for members and forces, and for MWFRS for reactions specified.
- 3) Provide adequate drainage to prevent water ponding.
- 4) *This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 5) All bearings are assumed to be SYP No.2 crushing capacity of 565.00 psi
- 6) Bearing at joint(s) 2 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 268 lb uplift at joint 2 and 159 lb uplift at joint 9.

LOAD CASE(S) Standard

Julius Lee
Truss Design Engineer
Florida PE No. 34868
1100 Coastal Bay Blvd
Boynton Beach, FL 33435

May 23, 2008

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE

This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	GIEBEIG HOMES - ST. JOHNS W/RP
L278347	T08	ROOF TRUSS	4	1	J1966929
Job Reference (optional)					

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Fri May 23 07:17:55 2008 Page 1




Plate Offsets (X,Y): [4:0-2-12,0-3-0], [11:0-6-0,0-3-0]

LOADING (psf)	SPACING	2-0-0	CSI	DEFL	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plates Increase	1.25	TC 0.39	Vert(LL)	0.21 11-12	>999	360	MT20	244/190
TCDL 7.0	Lumber Increase	1.25	BC 0.49	Vert(TL)	-0.34 11-12	>883	240		
BCLL 10.0	* Rep Stress Incr	YES	WB 0.54	Horz(TL)	0.13 10	n/a	n/a		
BCDL 5.0	Code FBC2004/TPI2002		(Matrix)					Weight: 130 lb	

LUMBER

TOP CHORD 2 X 4 SYP No.2
 BOT CHORD 2 X 4 SYP No.2
 WEBS 2 X 4 SYP No.3 *Except*
 W6 2 X 6 SYP No.1D

BRACING

TOP CHORD Structural wood sheathing directly applied or
 3-7-13 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 5-7-4 oc
 bracing.

REACTIONS (lb/size) 2=917/0-3-8, 10=817/0-3-8
 Max Horz 2=187(load case 6)
 Max Uplift 2=-276(load case 6), 10=-171(load case 7)

FORCES (lb) - Maximum Compression/Maximum Tension
 TOP CHORD 1-2=0/46, 2-3=-2537/1353, 3-4=-2492/1493, 4-5=-963/614, 5-6=-965/615,
 6-7=-317/165, 7-8=0/10, 7-10=-261/204
 BOT CHORD 2-12=-1252/2249, 11-12=-720/1325, 10-11=-485/896, 9-10=0/0
 WEBS 3-12=-216/240, 4-11=-627/465, 5-11=-311/517, 6-11=-174/176, 6-10=-856/524,
 4-12=-708/1197

JOINT STRESS INDEX

2 = 0.79, 3 = 0.33, 4 = 0.76, 5 = 0.73, 6 = 0.36, 7 = 0.75, 10 = 0.77, 11 = 0.53 and 12 = 0.63

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-02; 110mph (3-second gust); h=13ft; TCDL=4.2psf; BCDL=3.0psf; Category II; Exp B; enclosed; MWFRS and C-C Exterior(2) zone; Lumber DOL=1.60 plate grip DOL=1.60. This truss is designed for C-C for members and forces, and for MWFRS for reactions specified.

Julius Lane
 Truss Design Engineer
 Florida Reg No. 31868
 1109 Coastal Bay Blvd
 Boynton Beach, FL 33436

Continued on page 2

May 23, 2008

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE
 This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	GIEBEIG HOMES - ST. JOHNS W/RP
L278347	T08	ROOF TRUSS	4	1	J1966929
					Job Reference (optional)

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Fri May 23 07:17:55 2008 Page 2

NOTES

- 3) *This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 4) All bearings are assumed to be SYP No.2 crushing capacity of 565.00 psi
- 5) Bearing at joint(s) 2 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 276 lb uplift at joint 2 and 171 lb uplift at joint 10.

LOAD CASE(S) Standard

Julius Lee
Truss Design Engineer
Florida PE No. 34888
1400 Coastal Bay Blvd
Boynton Beach, FL 33435

May 23, 2008

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE

This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	GIEBEIG HOMES - ST. JOHNS W/RP
L278347	T09	ROOF TRUSS	1	1	J1966930
Job Reference (optional)					

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Fri May 23 07:17:56 2008 Page 1




Plate Offsets (X,Y): [2:0-1-13,Edge], [5:0-3-8,0-3-0]

LOADING (psf)	SPACING	2-0-0	CSI	DEFL	in (loc)	I/defl	L/d	PLATES	GRIP
TCLL 20.0	Plates Increase	1.25	TC 0.76	Vert(LL)	-0.28 11	>999	360	MT20	244/190
TCDL 7.0	Lumber Increase	1.25	BC 0.96	Vert(TL)	-0.58 9-11	>615	240	MT20H	187/143
BCLL 10.0	* Rep Stress Incr	NO	WB 0.88	Horz(TL)	0.19 8	n/a	n/a		
BCDL 5.0	Code FBC2004/TPI2002		(Matrix)						
									Weight: 149 lb

LUMBER

TOP CHORD 2 X 4 SYP No.2
BOT CHORD 2 X 4 SYP No.2
WEBS 2 X 4 SYP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied or 2-4-4 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 5-0-11 oc bracing.
WEBS T-Brace: 2 X 4 SYP No.3 - 6-8
Fasten T and I braces to narrow edge of web with 10d Common wire nails, 9in o.c., with 4in minimum end distance.
Brace must cover 90% of web length.

REACTIONS (lb/size) 8=2108/0-3-8, 2=2051/0-3-8
Max Horz 2=163(load case 5)
Max Uplift 8=-727(load case 4), 2=-641(load case 5)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=0/47, 2-3=-3862/1259, 3-4=-3411/1166, 4-5=-4456/1501, 5-6=-3299/1099, 6-7=-78/14, 7-8=-274/136
BOT CHORD 2-12=-1151/3359, 11-12=-1558/4437, 10-11=-1516/4297, 9-10=-1516/4297, 8-9=-929/2619
WEBS 3-12=-382/1241, 4-12=-1246/526, 4-11=0/190, 5-11=0/246, 5-9=-1342/561, 6-9=-315/1260, 6-8=-3085/1111

Julius Lee
Truss Design Engineer
Florida PE No. 34889
1100 Coastal Bay Blvd
Daytona Beach, FL 32118

JOINT STRESS INDEX

2 = 0.81, 3 = 0.73, 4 = 0.41, 5 = 0.79, 6 = 0.92, 7 = 0.59, 8 = 0.89, 9 = 0.92, 10 = 0.86, 11 = 0.41 and 12 = 0.79

Continued on page 2

May 23, 2008

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITTEK REFERENCE PAGE MII-7473 BEFORE USE
This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 563 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	GIEBEIG HOMES - ST. JOHNS W/RP
L278347	T09	ROOF TRUSS	1	1	J1966930
Job Reference (optional)					

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Fri May 23 07:17:56 2008 Page 2

NOTES

- 1) Wind: ASCE 7-02; 110mph (3-second gust); h=13ft; TCDL=4.2psf; BCDL=3.0psf; Category II; Exp B; enclosed; MWFRS; Lumber DOL=1.60 plate grip DOL=1.60.
- 2) Provide adequate drainage to prevent water ponding.
- 3) *This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 4) All plates are MT20 plates unless otherwise indicated.
- 5) All bearings are assumed to be SYP No.2 crushing capacity of 565.00 psi
- 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 727 lb uplift at joint 8 and 641 lb uplift at joint 2.
- 7) In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

LOAD CASE(S) Standard

- 1) Regular: Lumber Increase=1.25, Plate Increase=1.25
Uniform Loads (plf)
Vert: 1-3=-54, 3-7=-118(F=-64), 2-12=-10, 8-12=-22(F=-12)
Concentrated Loads (lb)
Vert: 12=-411(F)

Julius Lee
Truss Design Engineer
Florida PE No. 34868
1155 Coastal Bay Blvd
Boynton Beach, FL 33435

May 23, 2008

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE
This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 563 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	GIEBEIG HOMES - ST. JOHNS W/RP
L278347	T10	ROOF TRUSS	1	1	J1966931
Job Reference (optional)					

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Fri May 23 07:17:56 2008 Page 1




Plate Offsets (X,Y): [2:0-1-9,0-0-7]

LOADING (psf)	SPACING	2-0-0	CSI	DEFL	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plates Increase	1.25	TC 0.70	Vert(LL)	-0.20 9-10	>999	360	MT20	244/190
TCDL 7.0	Lumber Increase	1.25	BC 0.57	Vert(TL)	-0.37 9-10	>967	240		
BCLL 10.0	* Rep Stress Incr	YES	WB 0.53	Horz(TL)	0.07 9	n/a	n/a		
BCDL 5.0	Code FBC2004/TPI2002		(Matrix)						
									Weight: 155 lb

LUMBER

TOP CHORD 2 X 4 SYP No.2
BOT CHORD 2 X 4 SYP No.2
WEBS 2 X 4 SYP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied or 4-8-3 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 6-6-0 oc bracing.
WEBS T-Brace: 2 X 4 SYP No.3 - 5-12, 7-9
Fasten T and I braces to narrow edge of web with 10d Common wire nails, 9in o.c., with 4in minimum end distance.
Brace must cover 90% of web length.

REACTIONS (lb/size) 9=949/0-3-8, 2=1073/0-3-8
Max Horz 2=195(load case 6)
Max Uplift 9=-259(load case 5), 2=-260(load case 6)

FORCES (lb) - Maximum Compression/Maximum Tension
TOP CHORD 1-2=0/47, 2-3=-1758/878, 3-4=-1536/781, 4-5=-1346/760, 5-6=-1400/730, 6-7=-1400/730, 7-8=-58/13, 8-9=-170/118
BOT CHORD 2-12=-928/1504, 11-12=-881/1581, 10-11=-881/1581, 9-10=-631/1136
WEBS 3-12=-188/191, 4-12=-100/396, 5-12=-283/158, 5-10=-293/245, 7-10=-160/464, 7-9=-1308/743

Julius Lee
Truss Design Engineer
Florida PE No. 34869
1100 Coastal Bay Blvd.
Boynton Beach, FL 33435

JOINT STRESS INDEX

2 = 0.77, 3 = 0.33, 4 = 0.71, 5 = 0.40, 6 = 0.32, 7 = 0.46, 8 = 0.76, 9 = 0.58, 10 = 0.40, 11 = 0.59 and 12 = 0.56

Continued on page 2

May 23, 2008

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE
This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	GIEBEIG HOMES - ST. JOHNS W/RP
L278347	T10	ROOF TRUSS	1	1	J1966931
					Job Reference (optional)

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MITek Industries, Inc. Fri May 23 07:17:57 2008 Page 2

NOTES

- 1) Wind: ASCE 7-02; 110mph (3-second gust); h=13ft; TCDL=4.2psf; BCDL=3.0psf; Category II; Exp B; enclosed; MWFRS and C-C Exterior(2) zone; Lumber DOL=1.60 plate grip DOL=1.60. This truss is designed for C-C for members and forces, and for MWFRS for reactions specified.
- 2) Provide adequate drainage to prevent water ponding.
- 3) *This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 4) All bearings are assumed to be SYP No.2 crushing capacity of 565.00 psi
- 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 259 lb uplift at joint 9 and 260 lb uplift at joint 2.

LOAD CASE(S) Standard

Julius Lee
Truss Design Engineer
Florida PE No. 31893
1109 Coastal Bay Blvd
Boynton Beach, FL 33435

May 23,2008

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE

This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	GIEBEIG HOMES - ST. JOHNS W/RP
L278347	T11	ROOF TRUSS	1	1	J1966932
					Job Reference (optional)

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Fri May 23 07:17:57 2008 Page 1




Plate Offsets (X,Y): [2:0-0-10,Edge], [7:0-3-8,Edge]

LOADING (psf)	SPACING	2-0-0	CSI	DEFL	in	(loc)	I/defl	L/d	PLATES	GRIP
TCCL 20.0	Plates Increase	1.25	TC 0.52	Vert(LL)	-0.25	2-11	>999	360	MT20	244/190
TCDL 7.0	Lumber Increase	1.25	BC 0.62	Vert(TL)	-0.47	2-11	>756	240		
BCCL 10.0	* Rep Stress Incr	YES	WB 0.44	Horz(TL)	0.05	8	n/a	n/a		
BCDL 5.0	Code FBC2004/TPI2002		(Matrix)							
									Weight: 157 lb	

LUMBER

TOP CHORD 2 X 4 SYP No.2
 BOT CHORD 2 X 4 SYP No.2
 WEBS 2 X 4 SYP No.3 *Except*
 W5 2 X 4 SYP No.2

BRACING

TOP CHORD Structural wood sheathing directly applied or
 4-7-5 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 6-11-8 oc
 bracing.

REACTIONS (lb/size) 2=1073/0-3-8, 8=949/0-3-8

Max Horz 2=147(load case 6)

Max Uplift 2=-280(load case 6), 8=-163(load case 7)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=0/47, 2-3=-1730/929, 3-4=-1419/784, 4-5=-1220/765, 5-6=-1048/691,
 6-7=-1265/678, 7-8=-908/533

BOT CHORD 2-11=-814/1478, 10-11=-609/1264, 9-10=-609/1264, 8-9=-171/211

WEBS 3-11=-306/286, 4-11=-107/369, 5-11=-187/118, 5-9=-410/171, 6-9=-16/272,
 7-9=-326/850

JOINT STRESS INDEX

2 = 0.79, 3 = 0.33, 4 = 0.68, 5 = 0.39, 6 = 0.74, 7 = 0.64, 8 = 0.70, 9 = 0.37, 10 = 0.72 and 11 = 0.56

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-02; 110mph (3-second gust); h=13ft; TCCL=4.2psf, BCDL=3.0psf, Category II; Exp B; enclosed; MWFRS and C-C Exterior(2) zone; Lumber DOL=1.60 plate grip DOL=1.60. This truss is designed for C-C for members and forces, and for MWFRS for reactions specified.
- Provide adequate drainage to prevent water ponding.

Julius Lee
 Truss Design Engineer
 Florida PE No. 34888
 1100 Coastal Bay Blvd
 Boynton Beach, FL 33435

May 23, 2008

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE
 This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 563 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	GIEBEIG HOMES - ST. JOHNS W/RP
L278347	T11	ROOF TRUSS	1	1	J1966932
					Job Reference (optional)

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Fri May 23 07:17:57 2008 Page 2

NOTES

- 4) *This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 5) All bearings are assumed to be SYP No.2 crushing capacity of 565.00 psi
- 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 280 lb uplift at joint 2 and 163 lb uplift at joint 8.

LOAD CASE(S) Standard

Julius Lee
Truss Design Engineer
Florida PE No. 31868
1109 Coastal Bay Blvd
Boynton Beach, FL 33435

May 23, 2008


Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE
This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	GIEBEIG HOMES - ST. JOHNS W/RP
L278347	T12	ROOF TRUSS	1	1	J1966933
Job Reference (optional)					

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Fri May 23 07:17:58 2008 Page 1



LOADING (psf)	SPACING	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plates Increase	1.25	TC 0.41	Vert(LL)	0.28	14-15	>999	360	MT20	244/190
TCDL 7.0	Lumber Increase	1.25	BC 0.61	Vert(TL)	-0.52	10	>687	240		
BCLL 10.0	* Rep Stress Incr	YES	WB 0.50	Horz(TL)	0.26	8	n/a	n/a		
BCDL 5.0	Code FBC2004/TPI2002		(Matrix)						Weight: 172 lb	

LUMBER

TOP CHORD 2 X 4 SYP No.2
 BOT CHORD 2 X 4 SYP No.2 *Except*
 B5 2 X 4 SYP No.3
 WEBS 2 X 4 SYP No.3 *Except*
 W8 2 X 4 SYP No.1D
 OTHERS 2 X 4 SYP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied or 3-2-11 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 5-1-3 oc bracing.
 WEBS T-Brace: 2 X 4 SYP No.3 - 3-14, 4-12
 Fasten T and I braces to narrow edge of web with 10d Common wire nails, 9in o.c., with 4in minimum end distance.
 Brace must cover 90% of web length.
 JOINTS 1 Brace at Jt(s): 11

REACTIONS (lb/size) 2=1082/0-3-8, 8=979/0-3-8
 Max Horz 2=158(load case 6)
 Max Uplift 2=-287(load case 6), 8=-160(load case 7)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=0/46, 2-3=-3222/1660, 3-4=-1675/910, 4-5=-1317/807, 5-6=-1516/832, 6-7=-1919/940, 7-8=-983/522
 BOT CHORD 2-15=-1503/2876, 14-15=-1432/2723, 13-14=-642/1446, 12-13=-642/1446, 11-12=-783/1677, 9-11=0/197, 6-11=0/309, 9-10=0/0, 8-9=-67/4
 WEBS 3-15=-307/748, 3-14=-1333/822, 4-14=-175/461, 4-12=-281/107, 5-12=-125/397, 6-12=-419/254, 8-11=-28/129, 7-11=-708/1570

Julius Lee
 Truss Design Engineer
 Florida PE No. 34869
 1100 Coastal Bay Blvd.
 Boynton Beach, FL 33435

JOINT STRESS INDEX

2 = 0.74, 3 = 0.63, 4 = 0.76, 5 = 0.81, 6 = 0.46, 7 = 0.72, 8 = 0.46, 9 = 0.71, 10 = 0.33, 11 = 0.74, 12 = 0.56, 13 = 0.46, 14 = 0.43, 15 = 0.84 and 16 = 0.33

Continued on page 2

May 23, 2008

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE
 This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Oonofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	GIEBEIG HOMES - ST. JOHNS W/RP
L278347	T12	ROOF TRUSS	1	1	J1966933
Job Reference (optional)					

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Fri May 23 07:17:58 2008 Page 2

NOTES

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-02; 110mph (3-second gust); h=13ft; TCDL=4.2psf; BCDL=3.0psf; Category II; Exp B; enclosed; MWFRS and C-C Exterior(2) zone; Lumber DOL=1.60 plate grip DOL=1.60. This truss is designed for C-C for members and forces, and for MWFRS for reactions specified.
- 3) Provide adequate drainage to prevent water ponding.
- 4) *This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 5) All bearings are assumed to be SYP No.2 crushing capacity of 565.00 psi
- 6) Bearing at joint(s) 2 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 287 lb uplift at joint 2 and 160 lb uplift at joint 8.

LOAD CASE(S) Standard

Julius Lee
Truss Design Engineer
Florida P.E. No. 34888
1100 Coastal Bay Blvd.
Boynton Beach, FL 33435


May 23, 2008

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE

This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



6.300 s Feb 15 2006 MiTek Industries, Inc. Fri May 23 07:18:00 2008 Page 1



Builders
FirstSource

Job	Truss	Truss Type	Qty	Ply	GIEBEIG HOMES - ST. JOHNS W/RP
L278347	T13	ROOF TRUSS	1	1	J1966934
Job Reference (optional)					

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Fri May 23 07:18:00 2008 Page 2

NOTES

- 2) Wind: ASCE 7-02; 110mph (3-second gust); h=13ft; TCDL=4.2psf; BCDL=3.0psf; Category II; Exp B; enclosed; MWFRS and C-C Exterior(2) zone; Lumber DOL=1.60 plate grip DOL=1.60. This truss is designed for C-C for members and forces, and for MWFRS for reactions specified.
- 3) Provide adequate drainage to prevent water ponding.
- 4) *This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 5) All bearings are assumed to be SYP No.2 crushing capacity of 565.00 psi
- 6) Bearing at joint(s) 2 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 297 lb uplift at joint 2 and 172 lb uplift at joint 9.

LOAD CASE(S) Standard

Julius Lee
Truss Design Engineer
Florida PE No. 34898
1409 Coastal Bay Blvd.
Boynton Beach, FL 33435

May 23, 2008

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE

This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	GIEBEIG HOMES - ST. JOHNS W/RP
L278347	T14	ROOF TRUSS	2	1	J1966935
					Job Reference (optional)

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Fri May 23 07:18:01 2008 Page 2

NOTES

- 2) Wind: ASCE 7-02; 110mph (3-second gust); h=13ft; TCDL=4.2psf; BCDL=3.0psf; Category II; Exp B; enclosed; MWFRS and C-C Exterior(2) zone; Lumber DOL=1.60 plate grip DOL=1.60. This truss is designed for C-C for members and forces, and for MWFRS for reactions specified.
- 3) *This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 4) All bearings are assumed to be SYP No.2 crushing capacity of 565.00 psi
- 5) Bearing at joint(s) 2 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 303 lb uplift at joint 2 and 180 lb uplift at joint 9.

LOAD CASE(S) Standard

Julius Lane
Truss Design Engineer
Florida PE No. 24804
1400 Coastal Bay Blvd
Boynton Beach, FL 33435

May 23, 2008

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE

This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	GIEBEIG HOMES - ST. JOHNS W/RP
L278347	T15	ROOF TRUSS	4	1	J1966936
Job Reference (optional)					

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Fri May 23 07:18:01 2008 Page 1




Plate Offsets (X,Y): [4:0-3-0,0-3-0]

LOADING (psf)	SPACING		2-0-0	CSI	DEFL	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plates Increase		1.25	TC 0.42	Vert(LL)	-0.31 10-12	>999	360	MT20	244/190
TCDL 7.0	Lumber Increase		1.25	BC 0.70	Vert(TL)	-0.66 10-12	>540	240		
BCLL 10.0	* Rep Stress Incr	YES		WB 0.68	Horz(TL)	0.19 7	n/a	n/a		
BCDL 5.0	Code FBC2004/TPI2002			(Matrix)					Weight: 147 lb	

LUMBER

TOP CHORD 2 X 4 SYP No.2
BOT CHORD 2 X 4 SYP No.2
WEBS 2 X 4 SYP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied or 3-2-6 oc purlins.
BOT CHORD Rigid ceiling directly applied or 5-4-7 oc bracing.

REACTIONS

(lb/size) 2=1069/0-3-8, 7=1069/0-3-8
Max Horz 2=163(load case 6)
Max Uplift 2=-308(load case 6), 7=-289(load case 7)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=0/46, 2-3=-3166/1584, 3-4=-3107/1721, 4-5=-1248/759, 5-6=-1255/763,
6-7=-1704/907, 7-8=0/47
BOT CHORD 2-12=-1342/2823, 11-12=-784/1704, 10-11=-784/1704, 9-10=-620/1439,
7-9=-620/1439
WEBS 3-12=-192/230, 4-12=-727/1410, 4-10=-759/533, 5-10=-397/710, 6-10=-474/340,
6-9=0/185

JOINT STRESS INDEX

2 = 0.73, 3 = 0.33, 4 = 0.52, 5 = 0.75, 6 = 0.46, 7 = 0.74, 9 = 0.33, 10 = 0.56, 11 = 0.60 and 12 = 0.87

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-02; 110mph (3-second gust); h=13ft; TCDL=4.2psf; BCDL=3.0psf; Category II; Exp B; enclosed; MWFRS and C-C Exterior(2) zone; Lumber DOL=1.60 plate grip DOL=1.60. This truss is designed for C-C for members and forces, and for MWFRS for reactions specified.

Julius Lee
Truss Design Engineer
Florida PE No. 34888
1100 Coastal Bay Blvd
Boynton Beach, FL 33435

May 23, 2008

Continued on page 2

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE
This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	GIEBEIG HOMES - ST. JOHNS W/RP
L278347	T15	ROOF TRUSS	4	1	J1966936
Job Reference (optional)					

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Fri May 23 07:18:02 2008 Page 2

NOTES

- 3) *This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 4) All bearings are assumed to be SYP No.2 crushing capacity of 565.00 psi
- 5) Bearing at joint(s) 2 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 308 lb uplift at joint 2 and 289 lb uplift at joint 7.

LOAD CASE(S) Standard

Julius Lane
Truss Design Engineer
Florida PE No. 31803
1109 Coastal Bay Blvd.
Boynton Beach, FL 33426

May 23, 2008

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE

This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	GIEBEIG HOMES - ST. JOHNS W/RP J1966937
L278347	T16	ROOF TRUSS	1	1	Job Reference (optional)

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Fri May 23 07:18:02 2008 Page 1




Plate Offsets (X,Y): [4:0-3-0,0-3-0], [8:0-1-8,0-0-7]

LOADING (psf)	SPACING	2-0-0	CSI	DEFL	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plates Increase	1.25	TC 0.41	Vert(LL)	0.28 13-14	>999	360	MT20	244/190
TCDL 7.0	Lumber Increase	1.25	BC 0.59	Vert(TL)	-0.53 13-14	>681	240		
BCLL 10.0	* Rep Stress Incr	YES	WB 0.55	Horz(TL)	0.20 8	n/a	n/a		
BCDL 5.0	Code FBC2004/TPI2002		(Matrix)						
								Weight: 162 lb	

LUMBER

TOP CHORD 2 X 4 SYP No.2
BOT CHORD 2 X 4 SYP No.2
WEBS 2 X 4 SYP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied or 3-2-10 oc purlins.
BOT CHORD Rigid ceiling directly applied or 5-4-10 oc bracing.

REACTIONS

(lb/size) 2=1069/0-3-8, 8=1069/0-3-8
Max Horz 2=156(load case 6)
Max Uplift 2=-303(load case 6), 8=-282(load case 7)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=0/46, 2-3=-3158/1578, 3-4=-3118/1736, 4-5=-1332/807, 5-6=-1124/768,
6-7=-1330/776, 7-8=-1768/921, 8-9=0/47
BOT CHORD 2-14=-1338/2814, 13-14=-700/1600, 12-13=-375/1151, 11-12=-375/1151,
10-11=-657/1511, 8-10=-657/1511
WEBS 3-14=-235/266, 4-14=-813/1501, 4-13=-635/456, 5-13=-278/521, 6-11=-103/306,
7-11=-437/307, 7-10=0/201, 5-11=-226/106

JOINT STRESS INDEX

2 = 0.73, 3 = 0.33, 4 = 0.67, 5 = 0.28, 6 = 0.80, 7 = 0.46, 8 = 0.76, 10 = 0.33, 11 = 0.64, 12 = 0.62, 13 = 0.39 and 14 = 0.78

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-02; 110mph (3-second gust); h=13ft; TCDL=4.2psf; BCDL=3.0psf; Category II; Exp B; enclosed; MWFRS and C-C Exterior(2) zone; Lumber DOL=1.60 plate grip DOL=1.60. This truss is designed for C-C for members and forces, and for MWFRS for reactions specified.
- Provide adequate drainage to prevent water ponding.

Julius Lane
Truss Design Engineer
Florida Reg. No. 31868
1100 Coastal Bay Blvd
Boynton Beach, FL 33435

May 23, 2008

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITTEK REFERENCE PAGE MII-7473 BEFORE USE
This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Oonofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	GIEBEIG HOMES - ST. JOHNS W/RP J1966937
L278347	T16	ROOF TRUSS	1	1	Job Reference (optional)

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Fri May 23 07:18:02 2008 Page 2

NOTES

- 4) *This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 5) All bearings are assumed to be SYP No.2 crushing capacity of 565.00 psi
- 6) Bearing at joint(s) 2 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 303 lb uplift at joint 2 and 282 lb uplift at joint 8.

LOAD CASE(S) Standard

Julius Lee
Truss Design Engineer
Florida PE No. 24868
1400 Coastal Bay Blvd.
Boynton Beach, FL 33435

May 23, 2008

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE

This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	GIEBEIG HOMES - ST. JOHNS W/RP
L278347	T17	ROOF TRUSS	1	1	J1966938
Job Reference (optional)					

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Fri May 23 07:18:03 2008 Page 1




Plate Offsets (X,Y): [7:0-0-10,Edge]

LOADING (psf)	SPACING	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plates Increase	1.25	TC 0.40	Vert(LL)	0.27	11-12	>999	360	MT20	244/190
TCDL 7.0	Lumber Increase	1.25	BC 0.60	Vert(TL)	-0.48	7-9	>751	240		
BCLL 10.0	* Rep Stress Incr	YES	WB 0.43	Horz(TL)	0.21	7	n/a	n/a		
BCDL 5.0	Code FBC2004/TPI2002		(Matrix)						Weight: 148 lb	

LUMBER

TOP CHORD 2 X 4 SYP No.2
BOT CHORD 2 X 4 SYP No.2
WEBS 2 X 4 SYP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied or 3-3-3 oc purlins.
BOT CHORD Rigid ceiling directly applied or 5-4-5 oc bracing.
WEBS T-Brace: 2 X 4 SYP No.3 - 3-11
Fasten T and I braces to narrow edge of web with 10d Common wire nails, 9in o.c., with 4in minimum end distance.
Brace must cover 90% of web length.

REACTIONS (lb/size) 2=1069/0-3-8, 7=1069/0-3-8
Max Horz 2=144(load case 6)
Max Uplift 2=-293(load case 6), 7=-270(load case 7)

FORCES (lb) - Maximum Compression/Maximum Tension
TOP CHORD 1-2=0/46, 2-3=-3177/1592, 3-4=-1614/880, 4-5=-1258/781, 5-6=-1459/797, 6-7=-1749/947, 7-8=0/47
BOT CHORD 2-12=-1355/2836, 11-12=-1293/2685, 10-11=-527/1386, 9-10=-527/1386, 7-9=-681/1502
WEBS 3-12=-267/742, 3-11=-1352/795, 4-11=-175/421, 4-9=-282/110, 5-9=-104/367, 6-9=-274/263

Julius Lee
Truss Design Engineer
Florida PE No. 24888
1400 Coastal Bay Blvd
Boynton Beach, FL 33435

JOINT STRESS INDEX

2 = 0.73, 3 = 0.63, 4 = 0.75, 5 = 0.76, 6 = 0.33, 7 = 0.84, 9 = 0.56, 10 = 0.44, 11 = 0.44 and 12 = 0.82

Continued on page 2

May 23, 2008

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MH-7473 BEFORE USE
This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	GIEBEIG HOMES - ST. JOHNS W/RP J1966938
L278347	T17	ROOF TRUSS	1	1	Job Reference (optional)

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Fri May 23 07:18:03 2008 Page 2

NOTES

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-02; 110mph (3-second gust); h=13ft; TCDL=4.2psf; BCDL=3.0psf; Category II; Exp B; enclosed; MWFRS and C-C Exterior(2) zone; Lumber DOL=1.60 plate grip DOL=1.60. This truss is designed for C-C for members and forces, and for MWFRS for reactions specified.
- 3) Provide adequate drainage to prevent water ponding.
- 4) *This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 5) All bearings are assumed to be SYP No.2 crushing capacity of 565.00 psi
- 6) Bearing at joint(s) 2 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 293 lb uplift at joint 2 and 270 lb uplift at joint 7.

LOAD CASE(S) Standard

Julius Lee
Truss Design Engineer
Florida PE No. 34888
1400 Coastal Bay Blvd
Boynton Beach, FL 33435

May 23, 2008

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE


This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	GIEBEIG HOMES - ST. JOHNS W/RP
L278347	T18	ROOF TRUSS	1	1	J1966939
Job Reference (optional)					

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Fri May 23 07:18:04 2008 Page 1



LOADING (psf)	SPACING	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plates Increase	1.25	TC 0.27	Vert(LL)	-0.01	8	>999	360	MT20	244/190
TCDL 7.0	Lumber Increase	1.25	BC 0.15	Vert(TL)	-0.01	8	>999	240		
BCLL 10.0	* Rep Stress Incr	NO	WB 0.02	Horz(TL)	0.00	5	n/a	n/a		
BCDL 5.0	Code FBC2004/TPI2002		(Matrix)						Weight: 42 lb	

LUMBER

TOP CHORD 2 X 4 SYP No.2
BOT CHORD 2 X 4 SYP No.2
WEBS 2 X 4 SYP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (lb/size) 2=435/0-3-8, 5=435/0-3-8
Max Horz 2=-54(load case 6)
Max Uplift 2=-278(load case 5), 5=-278(load case 6)

FORCES (lb) - Maximum Compression/Maximum Tension
TOP CHORD 1-2=0/47, 2-3=-426/230, 3-4=-357/206, 4-5=-429/232, 5-6=0/47
BOT CHORD 2-9=-171/334, 8-9=-166/332, 7-8=-161/336, 5-7=-166/338
WEBS 3-8=-47/42, 4-8=-44/37, 3-9=-56/76, 4-7=-55/76

JOINT STRESS INDEX

2 = 0.57, 3 = 0.07, 4 = 0.07, 5 = 0.57, 7 = 0.05, 8 = 0.04 and 9 = 0.05

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-02; 110mph (3-second gust); h=13ft; TCDL=4.2psf; BCDL=3.0psf; Category II; Exp B; enclosed; MWFRS; porch left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60.
- Provide adequate drainage to prevent water ponding.
- *This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- All bearings are assumed to be SYP No.2 crushing capacity of 565.00 psi
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 278 lb uplift at joint 2 and 278 lb uplift at joint 5.

Continued on page 2

Julius Lee
Truss Design Engineer
Florida PE No. 24888
1350 Coastal Bay Blvd
Boynton Beach, FL 33435

May 23, 2008

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITTEK REFERENCE PAGE MII-7473 BEFORE USE
This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	GIEBEIG HOMES - ST. JOHNS W/RP
L278347	T18	ROOF TRUSS	1	1	J1966939
Job Reference (optional)					

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Fri May 23 07:18:04 2008 Page 2

NOTES

7) In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

LOAD CASE(S) Standard

1) Regular: Lumber Increase=1.25, Plate Increase=1.25

Uniform Loads (plf)

Vert: 1-3=-54, 3-4=-64(F=-10), 4-6=-54, 2-9=-10, 7-9=-12(F=-2), 5-7=-10

Concentrated Loads (lb)

Vert: 9=-48(F) 7=-48(F)

Julius Lee
Truss Design Engineer
Florida PE No. 24866
1400 Coastal Bay Blvd
Boynton Beach, FL 33435

May 23, 2008

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE

This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	GIEBEIG HOMES - ST. JOHNS W/RP
L278347	T19	ROOF TRUSS	2	1	J1966940
					Job Reference (optional)

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Fri May 23 07:18:05 2008 Page 1




Plate Offsets (X,Y): [2:0-2-4,0-1-8], [4:0-2-4,0-1-8]

LOADING (psf)	SPACING	2-0-0	CSI	DEFL	in	(loc)	I/defl	L/d	PLATES	GRIP
TCLL 20.0	Plates Increase	1.25	TC 0.29	Vert(LL)	0.03	4-5	>999	360	MT20	244/190
TCDL 7.0	Lumber Increase	1.25	BC 0.13	Vert(TL)	-0.02	4-5	>999	240		
BCLL 10.0	* Rep Stress Incr	YES	WB 0.04	Horz(TL)	-0.01	4	n/a	n/a		
BCDL 5.0	Code FBC2004/TPI2002		(Matrix)							
									Weight: 33 lb	

LUMBER

TOP CHORD 2 X 4 SYP No.2
BOT CHORD 2 X 4 SYP No.2
WEBS 2 X 4 SYP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 9-8-7 oc bracing.

REACTIONS (lb/size) 4=242/0-3-8, 2=389/0-3-8
Max Horz 2=74(load case 6)
Max Uplift 4=-155(load case 7), 2=-262(load case 6)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=0/47, 2-3=-341/525, 3-4=-335/514
BOT CHORD 2-5=-390/255, 4-5=-390/255
WEBS 3-5=-243/134

JOINT STRESS INDEX

2 = 0.67, 3 = 0.58, 4 = 0.67 and 5 = 0.10

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-02; 110mph (3-second gust); h=13ft; TCDL=4.2psf; BCDL=3.0psf; Category II; Exp B; enclosed; MWFRS and C-C Exterior(2) zone; porch left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60. This truss is designed for C-C for members and forces, and for MWFRS for reactions specified.
- *This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.

4) All bearings are assumed to be SYP No.2 crushing capacity of 565.00 psi

Continued on page 2

Julius Lee
Truss Design Engineer
Florida P.E. No. 34888
1400 Coastal Bay Blvd
Boynton Beach, FL 33435

May 23, 2008

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE
This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 563 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	GIEBEIG HOMES - ST. JOHNS W/RP
L278347	T19	ROOF TRUSS	2	1	J1966940
Job Reference (optional)					

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Fri May 23 07:18:05 2008 Page 2

NOTES

- 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 155 lb uplift at joint 4 and 262 lb uplift at joint 2.

LOAD CASE(S) Standard

Julius Lee
Truss Design Engineer
Florida PE No. 34888
1400 Coastal Bay Blvd
Boynton Beach, FL 33436

May 23, 2008

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE

This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	GIEBEIG HOMES - ST. JOHNS W/RP
L278347	T20	HIP	1	1	J1966941
Job Reference (optional)					

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Fri May 23 07:18:05 2008 Page 1




Plate Offsets (X,Y): [2:0-1-9,0-0-7], [5:0-1-9,0-0-7]

LOADING (psf)	SPACING	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plates Increase	1.25	TC 0.40	Vert(LL)	0.12	2-8	>999	360	MT20	244/190
TCDL 7.0	Lumber Increase	1.25	BC 0.42	Vert(TL)	-0.14	2-8	>999	240		
BCLL 10.0	* Rep Stress Incr	NO	WB 0.19	Horz(TL)	0.04	5	n/a	n/a		
BCDL 5.0	Code FBC2004/TPI2002		(Matrix)							
									Weight: 72 lb	

LUMBER

TOP CHORD 2 X 4 SYP No.2
BOT CHORD 2 X 4 SYP No.2
WEBS 2 X 4 SYP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied or 4-4-10 oc purlins.
BOT CHORD Rigid ceiling directly applied or 7-5-5 oc bracing.

REACTIONS

(lb/size) 2=1103/0-3-8, 5=1103/0-3-8
Max Horz 2=-77(load case 6)
Max Uplift 2=-595(load case 5), 5=-595(load case 6)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=0/47, 2-3=-1778/804, 3-4=-1526/770, 4-5=-1781/806, 5-6=0/47
BOT CHORD 2-8=-675/1504, 7-8=-684/1523, 5-7=-658/1507
WEBS 3-8=-262/480, 4-7=-303/592, 3-7=-146/159

JOINT STRESS INDEX

2 = 0.77, 3 = 0.87, 4 = 0.76, 5 = 0.77, 7 = 0.43 and 8 = 0.34

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-02; 110mph (3-second gust); h=13ft; TCDL=4.2psf; BCDL=3.0psf; Category II; Exp B; enclosed; MWFRS; porch left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60.
- Provide adequate drainage to prevent water ponding.
- *This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- All bearings are assumed to be SYP No.2 crushing capacity of 565.00 psi

Julius Lane
Truss Design Engineer
Florida Reg. No. 31888
1100 Coastal Bay Blvd
Boynton Beach, FL 33435

Continued on page 2

May 23,2008

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITTEK REFERENCE PAGE MII-7473 BEFORE USE
This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	GIEBEIG HOMES - ST. JOHNS W/RP
L278347	T20	HIP	1	1	J1966941
					Job Reference (optional)

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Fri May 23 07:18:06 2008 Page 2

NOTES

- 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 595 lb uplift at joint 2 and 595 lb uplift at joint 5.
- 7) In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

LOAD CASE(S) Standard

- 1) Regular: Lumber Increase=1.25, Plate Increase=1.25

Uniform Loads (plf)

Vert: 1-3=-54, 3-4=-118(F=-64), 4-6=-54, 2-8=-10, 7-8=-22(F=-12), 5-7=-10

Concentrated Loads (lb)

Vert: 8=-411(F) 7=-411(F)

Julius Lee
Truss Design Engineer
Florida P.E. No. 34868
1109 Coastal Bay Blvd.
Boynton Beach, FL 33435

May 23, 2008

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE
This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	GIEBEIG HOMES - ST. JOHNS W/RP
L278347	T21	QUEENPOST	3	1	J1966942
Job Reference (optional)					

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Fri May 23 07:18:06 2008 Page 1




Plate Offsets (X,Y): [2:0-1-12,Edge], [4:0-1-12,Edge]

LOADING (psf)	SPACING	2-0-0	CSI	DEFL	in	(loc)	I/defl	L/d	PLATES	GRIP
TCLL 20.0	Plates Increase	1.25	TC 0.51	Vert(LL)	0.24	4-6	>779	360	MT20	244/190
TCDL 7.0	Lumber Increase	1.25	BC 0.38	Vert(TL)	-0.14	4-6	>999	240		
BCLL 10.0	* Rep Stress Incr	YES	WB 0.14	Horz(TL)	-0.02	4	n/a	n/a		
BCDL 5.0	Code FBC2004/TPI2002		(Matrix)							
										Weight: 63 lb

LUMBER

TOP CHORD 2 X 4 SYP No.2
BOT CHORD 2 X 4 SYP No.2
WEBS 2 X 4 SYP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied or 6'-0" oc purlins.
BOT CHORD Rigid ceiling directly applied or 7'-1-0" oc bracing.

REACTIONS (lb/size) 2=619/0-3-8, 4=619/0-3-8
Max Horz 2=83(load case 6)
Max Uplift 2=-404(load case 6), 4=-404(load case 7)

FORCES (lb) - Maximum Compression/Maximum Tension
TOP CHORD 1-2=0/47, 2-3=-720/981, 3-4=-720/981, 4-5=0/47
BOT CHORD 2-6=-689/562, 4-6=-689/562
WEBS 3-6=-489/273

JOINT STRESS INDEX
2 = 0.77, 3 = 0.93, 4 = 0.77 and 6 = 0.19

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-02; 110mph (3-second gust); h=13ft; TCDL=4.2psf; BCDL=3.0psf; Category II; Exp B; enclosed; MWFRS and C-C Exterior(2) zone; porch left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60. This truss is designed for C-C for members and forces, and for MWFRS for reactions specified.
- *This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- All bearings are assumed to be SYP No.2 crushing capacity of 565.00 psi

Julius Lee
Truss Design Engineer
Florida PE No. 31868
1309 Coastal Bay Blvd
Boynton Beach, FL 33435

May 23, 2008

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE
This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	GIEBEIG HOMES - ST. JOHNS W/RP
L278347	T21	QUEENPOST	3	1	J1966942
Job Reference (optional)					

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Fri May 23 07:18:06 2008 Page 2

NOTES

- 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 404 lb uplift at joint 2 and 404 lb uplift at joint 4.

LOAD CASE(S) Standard

Julius Lee
Truss Design Engineer
Florida PE No. 24888
1400 Coastal Bay Blvd
Boynton Beach, FL 33435

May 23, 2008


Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE

This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719




Symbols

PLATE LOCATION AND ORIENTATION



*Center plate on joint unless dimensions indicate otherwise. Dimensions are in inches. Apply plates to both sides of truss and securely seat.



*For 4 x 2 orientation, locate plates 1/8" from outside edge of truss and vertical web.



*This symbol indicates the required direction of slots in connector plates.

PLATE SIZE

4 X 4


The first dimension is the width perpendicular to slots. Second dimension is the length parallel to slots.

LATERAL BRACING




Indicates location of required continuous lateral bracing.

BEARING



Indicates location of joints at which bearings (supports) occur.

Numbering System



JOINTS AND CHORDS ARE NUMBERED CLOCKWISE AROUND THE TRUSS STARTING AT THE LOWEST JOINT FARTHEST TO THE LEFT.

WEBS ARE NUMBERED FROM LEFT TO RIGHT

CONNECTOR PLATE CODE APPROVALS

BOCA	96-31, 96-67
ICBO	3907, 4922
SBCCI	9667, 9432A
WISC/DILHR	960022-W, 970036-N
NER	561



MITek Engineering Reference Sheet: MIT-7473



General Safety Notes

Failure to Follow Could Cause Property Damage or Personal Injury

1. Provide copies of this truss design to the building designer, erection supervisor, property owner and all other interested parties.
2. Cut members to bear tightly against each other.
3. Place plates on each face of truss at each joint and embed fully. Avoid knots and wane at joint locations.
4. Unless otherwise noted, locate chord splices at 1/4 panel length (± 6" from adjacent joint.)
5. Unless otherwise noted, moisture content of lumber shall not exceed 19% at time of fabrication.
6. Unless expressly noted, this design is not applicable for use with fire retardant or preservative treated lumber.
7. Camber is a non-structural consideration and is the responsibility of truss fabricator. General practice is to camber for dead load deflection.
8. Plate type, size and location dimensions shown indicate minimum plating requirements.
9. Lumber shall be of the species and size, and in all respects, equal to or better than the grade specified.
10. Top chords must be sheathed or purlins provided at spacing shown on design.
11. Bottom chords require lateral bracing at 10 ft. spacing, or less, if no ceiling is installed, unless otherwise noted.
12. Anchorage and / or load transferring connections to trusses are the responsibility of others unless shown.
13. Do not overload roof or floor trusses with stacks of construction materials.
14. Do not cut or alter truss member or plate without prior approval of a professional engineer.
15. Care should be exercised in handling, erection and installation of trusses.

© 1993 MITek® Holdings, Inc.

BRACING GROUP SPECIES AND GRADES:		
GROUP A:		
SPRUCE-PINE-TIR	MEM-PTR	
#1 / #2	STANDARD	#2
#3	STUD	STANDARD
DOUGLAS FIR-LARCH		
#3		#3
STUD		STUD
STANDARD		STANDARD
GROUP B:		
HUM-PTR		
#1 & BTR		
#1		
DOUGLAS FIR-LARCH		
#1		#1
#2		#2


LIVE LOAD DEFLECTION CRITERIA IS $L/240$.
 PROVIDE UPLIFT CONNECTIONS FOR 136 PLF OVER
 CONTINUOUS BEARING (6 PSF TC DEAD LOAD).

CABLE END SUPPORTS LOAD FROM 4' 0"
OUTDOCKERS WITH 2' 0" OVERHANG, OR 12"
PLYWOOD OVERHANG.

1" BRACING MUST BE A MINIMUM OF 80% OF WEB MEMBER LENGTH.

CHAIR VERTICAL PLATE SIZES	
VERTICAL LENGTH	NO SPLICE
LESS THAN 4' 0"	1X4 OR 2X3
GREATER THAN 4' 0", BUT LESS THAN 11' 6"	2X4
GREATER THAN 11' 6"	2-5X4

+ REFER TO COMMON TRUSS DESIGN FOR
PEAK, SPLICE, AND HEEL PLATES.



REFER TO CHART ABOVE FOR MAX GABLE VERTICAL LENGTH.

WARNING: REFER TO SECTION 4.00 (BUILDING, EQUIPMENT, MAINTENANCE, INSTALLATION AND REPAIRING) TO SEE 1-10 (BUILDING COMPONENT SAFETY INFORMATION), PUBLISHED BY IPI (TRUSS PLANT INSTITUTE), 583 DOWNEY RD., SUITE 200, WESTFIELD, NJ 07090 AND VITA AND TOLLS CONSULT OF AMERICA, 6300 ENTERPRISE LN., MADISON, WI 53719) FOR SAFETY PRACTICES PRIOR TO PERFORMING THESE FUNCTIONS. UNLESS OTHERWISE INDICATED, TOP CHORD SHALL HAVE PROPERLY ATTACHED TRUSS/ROOF PANELS AND BOTTOM CHORD SHALL HAVE PROPERLY ATTACHED RIGID CEILING.

JULIUS LEE'S
CONS. ENGINEERS P.A.

DELRAY BEACH, FL 33444-2161



-ENG

MAX. TOT. LD. 60 PSF

No: 34869
STATE OF FLORIDA

MAX. SPACING 24.0"

MAX GABLE VERTICAL LENGTH															
CABLE VERTICAL SPACING	2X4 SPECIES	BRACE GRADE	NO BRACES	(1) 1X4 "L" BRACE *		(1) 2X4 "L" BRACE *		(2) 2X4 "L" BRACE **		(1) 2X6 "L" BRACE *		(2) 2X6 "L" BRACE *		(2) 2X8 "L" BRACE **	
				GROUP A	GROUP B	GROUP A	GROUP B	GROUP A	GROUP B	GROUP A	GROUP B	GROUP A	GROUP B	GROUP A	GROUP B
24" O.C.	SPF	#1 / #2	3 2"	5 6"	6 8"	6 6"	6 9"	7 10"	8 0"	10 3"	10 7"	12 3"	12 7"		
			#3	3 1"	4 5"	4 5"	6 10"	6 10"	7 10"	7 10"	9 1"	9 1"	12 3"	12 3"	
			STUD	3 1"	4 6"	4 5"	5 10"	5 10"	7 10"	7 10"	9 1"	9 1"	12 3"	12 3"	
		HF	STANDARD	2 11"	3 9"	3 9"	6 0"	5 0"	6 9"	7 10"	7 10"	10 7"	10 7"	13 2"	13 2"
			#1	3 6"	5 6"	5 11"	6 6"	7 0"	7 10"	8 5"	10 3"	11 1"	12 3"	13 2"	
			#2	3 6"	5 6"	5 11"	6 6"	7 0"	7 10"	8 5"	10 3"	11 1"	12 3"	13 2"	
	DFL	#3	3 3"	4 6"	4 6"	6 0"	6 0"	7 10"	8 1"	9 4"	9 4"	12 3"	12 6"		
		STUD	3 3"	4 6"	4 6"	5 11"	5 11"	7 10"	8 0"	9 3"	9 3"	12 3"	12 6"		
		STANDARD	3 0"	3 10"	3 10"	6 1"	5 1"	6 11"	6 11"	8 0"	8 0"	10 10"	10 10"		
		#1 / #2	3 6"	6 4"	6 6"	7 6"	7 8"	8 11"	9 2"	11 9"	12 1"	14 0"	14 0"		
		#3	3 7"	5 5"	5 5"	7 2"	7 2"	8 11"	8 11"	11 2"	11 2"	14 0"	14 0"		
		STUD	3 7"	5 6"	5 5"	7 2"	7 2"	8 11"	8 11"	11 1"	11 1"	14 0"	14 0"		
16" O.C.	SPF	#1	3 7"	4 8"	4 8"	6 2"	6 2"	8 3"	8 3"	9 7"	9 7"	12 11"	12 11"		
			STUD	4 0"	6 4"	6 10"	7 6"	8 1"	8 11"	8 7"	11 9"	12 8"	14 0"	14 0"	
			STANDARD	3 11"	8 4"	8 10"	7 8"	7 4"	8 11"	9 7"	11 9"	12 8"	14 0"	14 0"	
		DFL	#2	3 9"	5 7"	6 7"	7 4"	7 4"	8 11"	9 6"	11 5"	11 6"	14 0"	14 0"	
			#3	3 9"	5 6"	5 6"	7 3"	7 3"	8 11"	9 5"	11 4"	11 4"	14 0"	14 0"	
			STUD	4 0"	4 9"	4 9"	6 3"	6 3"	8 10"	8 10"	10 1"	12 11"	13 4"	14 0"	
	HF	#1 / #2	3 6"	6 11"	7 2"	8 3"	8 6"	9 10"	9 10"	12 11"	12 11"	14 0"	14 0"		
		#3	3 11"	6 3"	6 3"	8 3"	8 3"	9 10"	9 10"	12 11"	12 11"	14 0"	14 0"		
		STUD	3 11"	6 3"	6 3"	8 3"	8 3"	9 10"	9 10"	12 10"	12 10"	14 0"	14 0"		
		STANDARD	3 11"	5 4"	5 4"	7 1"	7 1"	9 6"	9 6"	11 1"	11 1"	14 0"	14 0"		
		#1	4 5"	6 11"	7 6"	8 3"	8 3"	9 10"	10 7"	12 11"	13 11"	14 0"	14 0"		
		#2	4 4"	6 11"	7 6"	8 3"	8 3"	9 10"	10 7"	12 11"	13 11"	14 0"	14 0"		
DFL	#3	4 2"	6 4"	6 5"	8 3"	8 6"	9 10"	10 4"	12 11"	13 1"	14 0"	14 0"			
	STUD	4 2"	6 4"	6 4"	8 3"	8 6"	9 10"	10 4"	12 11"	13 1"	14 0"	14 0"			
	STANDARD	4 0"	5 6"	5 6"	7 3"	7 3"	9 9"	9 9"	11 4"	11 4"	14 0"	14 0"			
	#1	4 0"	5 6"	5 6"	7 3"	7 3"	9 9"	9 9"	11 4"	11 4"	14 0"	14 0"			
	#2	4 0"	5 6"	5 6"	7 3"	7 3"	9 9"	9 9"	11 4"	11 4"	14 0"	14 0"			
	STUD	4 0"	5 6"	5 6"	7 3"	7 3"	9 9"	9 9"	11 4"	11 4"	14 0"	14 0"			



REFER TO CHART ABOVE FOR MAX GABLE VERTICAL LENGTH.

DIAGONAL BRACE OPTION:
VERTICAL LENGTH MAY BE
DOUBLED WHEN DIAGONAL
BRACE IS USED. CONNECT
DIAGONAL BRACE FOR BRGf
AT EACH END. MAX WEB
TOTAL LENGTH IS 14".

HYDRAUNIC#4 TESTERS, EXTREME CARE FABRICATING, LAMINATING, SHOPPING, INST. ALUM. AND BRACING. REFER TO BC31-1-03 CHALLENGE COMPONENT SAFETY INFORMATION. PUL. ISSUED BY TPI CLASS PLATE INSTITUTE, 388 D'ONOFRIO RD., SUITE 200, MI, 48379 AND VITA LAMINATE TRUSS COUNCIL OF AMERICA, 6800 ENTERPRISE LAY, MARIETTA, VT 55359 FOR SPECIFIC PRACTICES PRIOR TO PERFORMING THESE FUNCTIONS. UNLESS OTHERWISE INDICATED, TOP CHORD SHALL HAVE PROPERLY ATTACHED STRUCTURAL PANELS AND BOTTOM CHORD SHALL HAVE A PROPERLY ATTACHED RIGID CEILING.

JULIUS LEE'S
CONS. ENGINEERS P.A.
1456 SW 4th AVENUE
DELRAY BEACH, FL. 33444-2161

No: 34868
STATE OF FLORIDA

MAX. TOT. LD. 60 PSF
MAX. SPACING 24.0"

REF	ASCE7-02-CAB13030
DATE	11/26/03
DWG	MITEK STD CABLE 30' E MT
-ENG	

BRACING GROUP SPECIES AND GRADES:

GROUP A:

SPRUCE-PINE-FIR		HEM-FIR	
#1 / #2	STANDARD	#2	STUD
#3	STUD	#3	STANDARD

43	BOUGLAS FR-LARCH
----	------------------

	STANDARD	STANDARD
1. The company has a clear vision and mission statement.		
2. The company has a strong leadership team.		
3. The company has a clear organizational structure.		
4. The company has a strong financial performance.		
5. The company has a strong customer base.		
6. The company has a strong brand identity.		
7. The company has a strong marketing strategy.		
8. The company has a strong sales team.		
9. The company has a strong product line.		
10. The company has a strong distribution network.		
11. The company has a strong research and development team.		
12. The company has a strong innovation culture.		
13. The company has a strong talent management strategy.		
14. The company has a strong corporate social responsibility program.		
15. The company has a strong sustainability strategy.		

GROUP B:

#1 & BTR	#1
----------	----

SOUTHERN PINE
#3

DOUGLAS FIR-LARCH
#1

24

CABLE TRUSS DETAIL NOTES:

LIVE LOAD DEPLETION CRITERIA IS $L/240$.

CONTINUOUS BEARING (6 PSF TC DEAD LOAD).

CABLE END SUPPORTS LOAD FROM 4' 0"

PLYWOOD OVERHANG.

ATTACH EACH "L" BRACE WITH 10d NAILS.

IN 18" END ZONES AND 4" O.C. BETWEEN ZONES.

IN 18" END ZONES AND 6" O.C. BETWEEN ZONES.

7. BRACING MUST BE A MINIMUM OF 80% OF WEB

Abstract

CABLE VERTICAL PLATE SIZES

VERTICAL LENGTH	NO SPICE
LESS THAN 4' 0"	1X4 DB. PK3

GREATER THAN 4' 0", BUT
LESS THAN 11' 0" 2X4

GREATER THAN 11' 6"	2.5X4
---------------------	-------

PEAK, SPLICE, AND HEBL PLATES.
+ HEELER: 10 COMMON CROSS DESIGN FOR

Journal of Management Inquiry 25(4) 391-407

Downloaded from <http://ajphaphysocpharm.sagepub.com/> at 11:06 11 November 2014

REF	ASCB7-02-CAB13030
-----	-------------------

DATE 11/26/03

DWG MITEK STD CABLE 30' E M7

-ENG


100

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80	81	82	83	84	85	86	87	88	89	90	91	92	93	94	95	96	97	98	99	100
---	---	---	---	---	---	---	---	---	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	-----


--	--

[illegible]


TYPICAL ATTIC TRUSS BRACING



TYPICAL ALTERNATE BRACING DETAIL FOR EXTERIOR FLAT GIRDER TRUSS




GABLE END TRUSS DETAIL



MINIMUM BC BRACING ON GABLE TRUSS. OTHER PERMANENT BRACING DESIGNS BY ARCHITECT OR EOR

TYPICAL WALL GIRDER VERTICAL WEB BRACING DETAIL



JULIUS LEE'S
CONS. ENGINEERS P.A.
1455 SW 41st AVENUE
DELRAT BEACH, FL 33444-2161

No: 34866
STATE OF FLORIDA

TOP	CHORD	2X4	#2	OR	BETTER
BOT	CHORD	2X4	#2	OR	BETTER
	WEBS	2X4	#3	OR	BETTER

SPACE PIGGYBACK VERTICALS AT 4' OC MAX.

PIGGYBACK BOTTOM CHORD MAY BE OMITTED. ATTACH VERTICAL WEBS TO TRUSS TOP CHORD WITH 1.5X3 PLATE.



REFER TO ENGINEER'S SEALED DESIGN FOR REQUIRED PURLIN SPACING

110 MPH WIND, 30' MEAN HGT, ASCE 7-02, CLOSED BLDG
LOCATED ANYWHERE IN POE 1 MI FROM COAST

ENCLOSED BLDG, LOCATED ANYWHERE IN ROOF
WIND TC DI-5 PSF WIND RC DI-5 PSF

FRONT FACE (B,*) PLATES MAY BE OFFSET FROM BACK FACE PLATES AS LONG AS BOTH FACES ARE SPACED 4' OC MAX.

130 MPH WIND, 30' MEAN HGT, ASCC 7-02, CLOSED
BLDG, LOCATED ANYWHERE IN ROOF, CAT II, EXP. C,
WIND TC DL=6 PSF, WIND BC DL=6 PSF



*ATTACH PIGGYBACK WITH 3X8 TRULOX OR ALPINE PIGGYBACK SPECIAL PLATE

INVESTIGATIONS REVEAL EXTREME CARE IN FABRICATING, HANDLING, SHIPPING, INSTALLING AND BRACING. REFER TO BEST-1 BUILDING COMPONENT SAFETY INFORMATION, PUBLISHED BY THE STEEL PLATE INSTITUTE, 368 DOWNSIDE RD., SUITE 20, MANASSAS, VA 22079 AND AISC CROD TRUSS COUNCIL OF AMERICA, 630 ENTERPRISE DR. MANASSAS, VA 22079 FOR SAFETY PRACTICES PRIOR TO PERFORMING THESE FUNCTIONS. TAISES OTHERWISE INDICATED, TOP CROD SHALL HAVE PROPERLY ATTACHED STRUCTURAL PLATES AND BOTTOM CROD SHALL HAVE A PROPERLY ATTACHED RIBBID CEILING.

THIS DRAWING REPLACES DRAWINGS 634.016 634.017 & 647.045


JOINT TYPE	SPANS UP TO			
	30'	34'	38'	52'
A	2X4	2.5X4	2.5X4	3X6
B	4X6	5X6	5X6	5X6
C	1.5X3	1.5X4	1.5X4	1.5X4
D	5X4	5X5	5X5	5X6
E	4X6 OR 3X6 TRUSS AT 4' OC, ROTATED VERTICALLY			

ATTACH TRULOX PLATES WITH (6) 0.120" X 1.375" NAILS, OR EQUAL, PER FACE PER PLY. (4) NAILS IN EACH MEMBER TO BE CONNECTED. REFER TO DRAWING 160 TL FOR TRULOX INFORMATION.

WEB BRACING CHART	
WEB LENGTH	REQUIRED BRACING
0" TO 7'9"	NO BRACING
7'9" TO 10'	1x4 "T" BRCE. SAME GRADE, SPECIES AS WEB MEMBER. OR BETTER, AND 80% LENGTH OF WEB MEMBER. ATTACH WITH 3d NAILS AT 4" OC.
10' TO 14'	2x4 "T" BRCE. SAME GRADE, SPECIES AS WEB MEMBER. OR BETTER, AND 80% LENGTH OF WEB MEMBER. ATTACH WITH 16d NAILS AT 4" OC.

*** PIGGYBACK SPECIAL PLATE**

ATTACH TEETH TO THE PIGBACK AT THE TIME OF FABRICATION. ATTACH TO SUPPORTING TRUSS WITH (4) 0.120" X 1.375" NAILS PER FACE PER PLY. APPLY PIGBACK SPECIAL PLATE TO EACH TRUSS FACE AND SPACE 4" OC OR LESS.



JULIUS LEH'S
CONS. ENGINEERS P.A.

1400 SW 4th AVENUE
DELRAY BEACH, FL. 33444-2161

MAX LOADING	REF	PIGGYBACK
-------------	-----	-----------

REF PIGGYBACK

55 PSF AT
1.33 DUR. FAC.

DRWG MITEK STD PIGGY

1.25 DUR. FAC.

210

1.15 DUR. FAC.

No: 34889
STATE OF FLORIDA

SPACING

1000000

TOP CHORD 2X4 SP #2 OR SPF #1/#2 OR BETTER.
BOT CHORD 2X3(*) OR 2X4 SP #2N OR SPF #1/#2 OR BETTER.
WEBS 2X4 SP #3 OR BETTER.

- UNLESS SPECIFIED ON ENGINEER'S SEALED DESIGN, APPLY 1X4 "T"-BRACE, 80% LENGTH OF WEB, VALLEY WEB, SAME SPECIES AND GRADE OR BETTER, ATTACHED WITH 8d BOX (0.13" X 2.5") NAILS AT 6" OC, OR CONTINUOUS LATERAL BRACING EQUALLY SPACED, FOR VERTICAL VALLEY WEBS GREATER THAN 7'9".

MAXIMUM VALLEY VERTICAL HEIGHT MAY NOT EXCEED 120'.




TOP CHORD OF TRUSS BENEATH VALLEY SET MUST BE BRACED WITH:
PROPERLY ATTACHED, RATED SHEATHING APPLIED PRIOR TO VALLEY TRUSS
INSTALLATION

PURLINS AT 24" OC OR AS OTHERWISE SPECIFIED ON ENGINEERS' SEALED DESIGN OR BY VALLEY TRUSSES USED IN LIEU OF PURLIN SPACING AS SPECIFIED ON ENGINEERS' SEALED DESIGN.

NOTE THAT THE PURLIN SPACING FOR BRACING THE TOP CHORD OF THE TRUSS BENEATH THE VALLEY IS MEASURED ALONG THE SLOPE OF THE TOP CHORD.

++ LARGER SPANS MAY BE BUILT AS LONG AS THE VERTICAL HEIGHT DOES NOT EXCEED 12'0".

BOTTOM CHORD MAY BE SQUARE OR PITCHED CUT AS SHOWN



SUPPORTING TRUSSES AT 24" OC MAXIMUM SPACING.

THIS DRAWING REPLACES DRAWING A105

AND WHEN OTHERS REQUIRE EXTREME CARE FABRICATING, HOLDING, SHIPPING, INSTALLING AND BRACING. REFER TO BEST-10 BUILDING EQUIPMENT SAFETY INFORMATION, PUBLISHED BY THE FLAT IRON INSTITUTE, 580 DORCHESTER RD., SUITE 200, MAINTON, VA 53799 AND VITA-GLASS TRUSS COUNCIL OF AMERICA, 6300 WESTVIEW DR., MAINTON, VA 53799 FOR SAFETY PRACTICES PRIOR TO PERFORMING THESE FUNCTIONS. UNLESS OTHERWISE INDICATED, TOP CHORD SHALL HAVE PROPERLY ATTACHED STRUCTURAL PANELS AND BOTTOM CHORD SHALL HAVE A PROPERLY ATTACHED RIGID CEILING.

JULIUS LEE
CONS. ENGINEERS P.A.

REF	VALLEY DETAIL	DATE	11/26/03
DRWG	VALTRUSS1103		
BC DL	5	PSF	
BC LL	0	PSF	
TOT. LD.	32	40	PSF

No: 34868
STATE OF FLORIDA

TOE-NAIL DETAIL

TOE-NAILS TO BE DRIVEN AT AN ANGLE OF APPROXIMATELY THIRTY DEGREES WITH THE PIECE AND STARTED APPROXIMATELY ONE-THIRD THE LENGTH OF THE NAIL FROM THE END OF THE MEMBER.

PER ANSI/AF&PA NDS-2001 SECTION 12.4.1 - EDGE DISTANCE, END DISTANCE, SPACING, EDGE DISTANCES, END DISTANCES AND SPACINGS FOR NAILS AND SPIKES SHALL BE SUFFICIENT TO PREVENT SPLITTING OF THE WOOD.



THE NUMBER OF TOE-NAILS TO BE USED IN A SPECIFIC APPLICATION IS DEPENDENT UPON PROPERTIES FOR THE CHORD SIZE, LUMBER SPECIES, AND NAIL TYPE. PROPER CONSTRUCTION PRACTICES AS WELL AS GOOD JUDGEMENT SHOULD DETERMINE THE NUMBER OF NAILS TO BE USED.

THIS DETAIL DISPLAYS A TOE-NAILED CONNECTION FOR JACK FRAMING INTO A SINGLE OR DOUBLE PLY SUPPORTING GIRDER.

MAXIMUM VERTICAL RESISTANCE OF 16d (0.162"x3.5") COMMON TOE-NAILS

NUMBER OF TOE-NAILS	SOUTHERN PINE		DOUGLAS FIR-LARCH		HEM-FIR		SPRUCE PINE FIR	
	1 PLY	2 PLYS	1 PLY	2 PLYS	1 PLY	2 PLYS	1 PLY	2 PLYS
2	187#	256#	181#	234#	156#	203#	154#	189#
3	298#	383#	271#	351#	234#	304#	230#	298#
4	394#	511#	361#	468#	312#	406#	307#	397#
5	493#	639#	452#	585#	390#	507#	384#	496#

ALL VALUES MAY BE MULTIPLIED BY APPROPRIATE DURATION OF LOAD FACTOR.



ALTERNATIVE CONDITION

THIS DRAWING REPLACES DRAWING 784040

NOTES: TRUSSES REQUIRE EXTREME CARE IN FABRICATING, HANDLING, SHIPPING, INSTALLING AND BRACING. AFTER TOE-NAILING, TRUSSES MUST BE PROTECTED FROM EXCESSIVE MOISTURE. TRUSSES OF AMERICA, 6500 ENTERPRISE LN, MADISON, VI 30719 FOR SAFETY PRACTICES PRIOR TO PERFORMING THESE FUNCTIONS. UNLESS OTHERWISE INDICATED, TOP CHORD SHALL HAVE PROPERLY ATTACHED STRUCTURAL PANELS AND BOTTOM CHORD SHALL HAVE A PROPERLY ATTACHED RIGID CEILING.

JULIUS LEE'S
CONS. ENGINEERS P.A.
1445 SW 4TH AVENUE
DELMAR BEACH, FL 33444-2161

No: 34869
STATE OF FLORIDA


TC LL	PSF	REF	TOE-NAIL
TC DL	PSF	DATE	09/12/07
BC DL	PSF	DRWG	CNTONAIL1103
BC LL	PSF	-ENG	JL
TOT. LD.	PSF		
DUR. FAC.	1.00		
SPACING			

1/2" DIAMETER BOLT SPACING FOR LOAD APPLIED PARALLEL TO GRAIN.

* GRADE AND SPECIES AS SPECIFIED ON THE ALPINE DESIGN.
BOLT HOLES SHALL BE A MINIMUM OF 1/32" TO A MAXIMUM OF 1/16" LARGER THAN BOLT DIAMETER.

TYPICAL LOCATION OF 1/2" DIAMETER THRU BOLTS. BOLT QUANTITIES AS NOTED ON SEALED DESIGN MUST BE APPLIED IN ONE OF THE PATTERNS SHOWN BELOW.

WASHERS REQUIRED UNDER BOLT HEAD AND NUT



2X6 DETAIL

2X8 DETAIL

THIS DRAWING REPLACES DRAWING A828.016

UNLESS OTHERWISE SPECIFIED, TRUSSES REQUIRE EXTERIOR GRADE, IN FABRICATING, HANDLING, SUPPORTING, INSTALLING AND BRACING. REFER TO DEPT. OF BUILDING CODES FOR TRUSS INFORMATION. PUBLISHED BY THE AMERICAN INSTITUTE OF STEEL CONSTRUCTION, INC., 530 NORTH DEARBORN STREET, CHICAGO, ILL. 60610. THIS DRAWING IS THE PROPERTY OF THE AMERICAN INSTITUTE OF STEEL CONSTRUCTION, INC. AND IS NOT TO BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, INCLUDING PHOTOCOPYING, RECORDING, OR BY ANY INFORMATION STORAGE AND RETRIEVAL SYSTEM, WITHOUT PERMISSION IN WRITING FROM THE AMERICAN INSTITUTE OF STEEL CONSTRUCTION, INC. UNLESS OTHERWISE INDICATED, THE DESIGN SHALL HAVE A PROPERLY ATTACHED STRUCTURAL PANELS AND BOTTOM CHORD SHALL HAVE A PROPERLY ATTACHED RIGID CEILING.

JULIUS LEE'S
CONS. ENGINEERS P.A.
1405 W. 4TH AVENUE
DELRAY BEACH, FL 33444-2161

No. 34889
STATE OF FLORIDA

TC LL	PSF	REF	BOLT SPACING
BC DL	PSF	DATE	11/26/03
BC LL	PSF	DRWG	CNBOLTSPI103
TOT. LD.	PSF	-ENG	JL
DUR. FAC.			
SPACING			

TRULOX CONNECTION DETAIL


11 GAUGE (0.120" X 1.375") NAILS REQUIRED FOR TRULOX PLATE ATTACHMENT. FILL ROWS COMPLETELY WHERE SHOWN (Φ).

* NAILS MAY BE OMITTED FROM THESE ROWS.

THIS DETAIL MAY BE USED WITH SO. PINE, DOUGLAS-FIR OR HEM-FIR CHORDS WITH A MINIMUM 1.00 DURATION OF LOAD OR SPRUCE-PINE-FIR CHORDS WITH A MINIMUM 1.15 DURATION OF LOAD. CHORD SIZE OF BOTH TRUSSES MUST EXCEED THE TRULOX PLATE WIDTH.


TRULOX PLATE IS CENTERED ON THE CHORDS AND BENT BETWEEN NAIL ROWS.

REFER TO ENGINEER'S SEALED DESIGN REFERENCING THIS DETAIL FOR LUMBER, PLATES, AND OTHER INFORMATION NOT SHOWN.



MINIMUM 3X6 TRULOX PLATE

TRULOX PLATE SIZE	REQUIRED NAILS PER TRUSS	MAXIMUM LOAD UP OR DOWN
3X6	9	350 #
5X6	15	990 #



MINIMUM 5X6 TRULOX PLATE

THIS DRAWING REPLACES DRAWINGS 1,158,989 1,158,989/R 1,164,844 1,162,217 1,162,017 1,159,154 & 1,151,524


WARNING: TRUSSES REQUIRE EXTREME CARE IN FABRICATING, HANDLING, SHIPPING, INSTALLING AND BRACING. REFER TO THE TRULOX DESIGN MANUAL FOR THE LATEST TRUSS CONSTRUCTION STANDARDS. TRULOX TRUSSES ARE DESIGNED FOR USE IN THE UNITED STATES OF AMERICA. 6300 ENTERPRISE LN, WATSON, VI 33719. DO NOT USE TRULOX TRUSSES FOR OTHER STRUCTURAL FUNCTIONS. UNLESS OTHERWISE INDICATED, TOP CHORD SHALL HAVE PROPERLY ATTACHED STRUCTURAL PANELS AND BOTTOM CHORD SHALL HAVE A PROPERLY ATTACHED RIGID CEILING.

JULIUS LEE'S
CONS. ENGINEERS P.A.
1455 SW 4th AVENUE
DELRAY BEACH, FL 33444-2181


No: 34869
STATE OF FLORIDA

REF	TRULOX
DATE	11/26/03
DRWG	CNTRULOX1103
-ENG	JL

**STRONG BACK DETAIL
SYSTEM-42 OR FLAT TRUSS**



**ALTERNATE DETAIL FOR
STRONG BACK WITH VERTICAL
NOT LINING UP**



JULIUS LEE'S
CONS. ENGINEERS P.A.
1456 SW 4th AVENUE
DEERAT BEACH, FL 33444-2661

No: 34669
STATE OF FLORIDA

CERTIFICATE OF OCCUPANCY

OCCUPANCY

COLUMBIA COUNTY, FLORIDA

Department of Building and Zoning Inspection

This Certificate of Occupancy is issued to the below named permit holder for the building and premises at the below named location, and certifies that the work has been completed in accordance with the Columbia County Building Code.

Parcel Number 11-4S-16-02911-313

Building permit No. 000027921

Use Classification SFD/UTILITY

Fire: 12.84

Permit Holder B. TRENT GIEBEIG

Waste: 33.50

Owner of Building PETE GIEBEIG

Total: 46.34

Location: 170 SW VANN COURT., LAKE CITY, FL

Date: 08/16/2010



Harry Dickel

Building Inspector



POST IN A CONSPICUOUS PLACE
(Business Places Only)



6/12 PITCH
2'0" O/H



BEARING HEIGHT SCHEDULE:

	8'-0"
	9'-6"

NOTES:

- 1) REFER TO MD 91 (RECOMMENDATIONS FOR BRACING INSTALLATION AND TEMPORARY BRACING) FOR BRACING REQUIREMENTS.
- 2) ALL TRUSSES INCLUDING TRUSSES LARGER THAN SHOWN ON THIS PLAN SHALL BE DESIGNED AND DETAIL CHECKED OR REFER TO DETAIL WORK FOR ALTERNATE BRACING REQUIREMENTS.
- 3) ALL WALLS ARE TO BE CONVENTIONALLY FRAMED BY RAFTER.
- 4) ALL TRUSSES ARE DESIGNED FOR 2" OC. RANDOM SPACING, UNLESS OTHERWISE NOTED.
- 5) ALL WALLS SHOWN ON PLACEMENT PLAN ARE CONSIDERED TO BE LIND. DESIGN, UNLESS OTHERWISE NOTED.
- 6) 5/8" TRUSSES MUST BE INSTALLED WITH THE TOP BEING UP.
- 7) ALL EDOF TRUSSES HANGERS TO BE SHOWN AS 5/8" UNLESS OTHERWISE NOTED. ALL TRUSSES HANGERS TO BE SHOWN AS 5/8" UNLESS OTHERWISE NOTED.
- 8) BEARING HEIGHTS (B.H.) TO BE DETERMINED BY BUILDER.

SHOP DRAWING APPROVAL

THIS LAYOUT IS THE SOLE SOURCE FOR INFORMATION OF TRUSSES AND WORKS ALL TRUSSES, ADDITIONAL OR OTHER TRUSSES, LAYOUTS, BEARING AND APPROVAL OF THIS LAYOUT, MUST BE OBTAINED BEFORE ANY TRUSSES ARE TO BE BUILT. VERIFY ALL CONDITIONS TO BEING AGAINST CHANGES THAT WILL BE EXACT IN EXISTING CHANGES TO THIS.

Special bearing for: _____

Approved by: _____ Date: _____



PHONE: 904-437-3344 FAX: 904-437-3944

PHONE: 904-437-3344 FAX: 904-437-3944

PHONE: 904-437-3344 FAX: 904-437-3944

PHONE: 904-437-3344 FAX: 904-437-3944

PHONE: 904-437-3344 FAX: 904-437-3944

PHONE: 904-437-3344 FAX: 904-437-3944

PHONE: 904-437-3344 FAX: 904-437-3944

PHONE: 904-437-3344 FAX: 904-437-3944

PHONE: 904-437-3344 FAX: 904-437-3944

PHONE: 904-437-3344 FAX: 904-437-3944

PHONE: 904-437-3344 FAX: 904-437-3944

PHONE: 904-437-3344 FAX: 904-437-3944

PHONE: 904-437-3344 FAX: 904-437-3944

PHONE: 904-437-3344 FAX: 904-437-3944