Lyleig

## A & B Well Drilling, Inc.

5673 NW Lake Jeffery Road Lake City, FL, 32055

(O) 386-758-3409

(F) 386-758-3410

(C) 386-623-3151

8/1/2011

To: Columbia County Building Department				
Description of well to be installed for Customer: Sandaujs				
Located at Address: Wilson Spring Regald				
1 hp 15 GPM Submersible Pump, 1 1/4" drop pipe, 86 gallon captive tank and back				
flow prevention, With SRWMD permit.				
Broce Erh				
Sincerely				
Bruce Park				
President				

• • • • • • • • • • • • • • • • • • • •		
1100-600 CATION FOR ONISIT	STATE OF FLORIDA DEPARTMENT OF HEALTH E SEWAGE DISPOSAL SYSTEM CONSTRU	ICTION PERMIT
APPLICATION FOR ONST	Permit Application Nu	
	Leittif Abbiterion Me	
SANdquiss	PART II - SITEPLAN	
v	9.	10
Scale: 1 inch = 40 feet.		
3/6	No RTH	122
	362	=SIDPE
1 of 40	41, 50, 1968	100
1 Was	41/ 52	
	De Las	3u
Notes: SER ATTACHED		
Motes:		
A 1	- A	
Site Plan submitted by:	NT	MASTER CONTRACTOR
Plan Approved X	Not Approved	Date SISI
	Columnation	County Health Department
ALL CHANGES MUST I	BE APPROVED BY THE COUNTY HEALTH	DEPARTMENT
\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \		Page 2 of 4
OH 4015, 0899 (Checletes previous editions which ma (Stock Number: 5744-082-4615-6)	(F)	• • • • • • • • • • • • • • • • • • • •

## **Columbia County Building Department Culvert Permit**

## Culvert Permit No. 000001903

DATE $08/1$	0/2011 PARCEL ID #	31-65-16-04013-001	
APPLICANT	DALE BURD	PHONE 386-49	7-2311
ADDRESS _	PO BOX 39	FORT WHITE	FL 32038
OWNER CH	HRISTINE SANDQUIST	PHONE 515-68	1-3498
ADDRESS 20	009 SW WILSON SPRINGS RD	FORT WHITE	FL 32038
CONTRACTO	R WENDELL CREWS	PHONE 352-35	1-6100
LOCATION O	F PROPERTY 47S,R ON WILSON SPRING	GS, 1.8 MILES ON RIGHT	
SUBDIVISION	//LOT/BLOCK/PHASE/UNIT		
	a- 0		
SIGNATURE			
	INSTALLATION REQUIREMENTS	<u>S</u>	
X	Culvert size will be 18 inches in diamete driving surface. Both ends will be mitere thick reinforced concrete slab.	er with a total lenght of 32 feet,	leaving 24 feet of poured with a 4 inch
	INSTALLATION NOTE: Turnouts will be a) a majority of the current and existing b) the driveway to be served will be parturnouts shall be concrete or paved concrete or paved driveway, whicheve current and existing paved or concrete.	g driveway turnouts are paved eved or formed with concrete. a minimum of 12 feet wide or ver is greater. The width shall o	the width of the
	Culvert installation shall conform to the	e approved site plan standards.	
	Department of Transportation Permit in	stallation approved standards.	
	Other		

ALL PROPER SAFETY REQUIREMENTS SHOULD BE FOLLOWED DURING THE INSTALATION OF THE CULVERT.

135 NE Hernando Ave., Suite B-21 Lake City, FL 32055

Phone: 386-758-1008 Fax: 386-758-2160

Amount Paid 25.00

